



Product Description

Vibra-TITE 137 High Temp-High Strength Threadlocker is a red single component anaerobic threadlocker. 137 joins threaded parts exposed to operating temperatures up to 450°F. It offers excellent performance at temperatures more the 150° higher than other threaded locking products because of its enhanced chemistry.

Typical Applications

Applications include high temperature locking and sealing of studs, nuts, screws, bolts, and fittings. Parts are locked and sealed against leakage, contamination and corrosion. The higher viscosity is more suitable for large diameter, coarse threaded parts. It is recommended for parts that do not require routine maintenance as disassembly is difficult and may require heat.

Instructions for Use

Ensure parts are clean, dry and free from oil and grease.

Procedure for Application

Product is normally hand applied from the bottle onto threaded parts.

Compatible Primers

Primers such as Vibra-TITE Excel 611 (Primer N) or Excel 612 (Primer T) can be used. The use of primers can result in lower strength and performance should be tested after full cure.

Technical Features

Resin:..... Dimethylacrylate
Color:.....Red
Fixture Speed w/Primer.....<5 seconds
Fixture Speed w/out Primer 30 min. @ 77°F
Viscosity (Thixotropic)..... 9500 cps

Gap Fill.....0.007"
Shelf Life.....12 months @ 68°F
Max. Operating Temp..... -65°F to +450°F

Cured Performance

Full Cure Time.....24 hours @ 68°F
Typical Breakaway Strength..150-250 in.lbs.
Typical Prevailing Strength...50-150 in.lbs.

Presentation

Bottles.....10ml, 50ml, 250ml and liter

General Information

Storage

Product should be stored in a cool and dry location at temperatures between -10 °C to 30 °C. Optimal storage is 22±4°C. Shelf life is 18 months from date of manufacture when stored at 22±4°C.

Note

Vibra-TITE 137 provides a lubricating ability during assembly and after curing results in medium to high locking strength. Not recommended for use with use with most plastics as stress cracking can occur. Excellent environmental and chemical resistance.

Health & Safety in use

IRRITANT: Contains Methacrylate Esters which may irritate eyes, respiratory organs and skin. In case of contact with the skin, wash immediately with plenty of water.