

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

1 Identification

- Product identifier

- **Trade name:** Vibra-TITE® Thread Sealant
- **Synonyms:** 420 Controlled Strength - Slow Cure Thread Sealant
- **Part number:** VT420
- **Application of the substance / the mixture**
Thread Sealant
Sealing
Sealant

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**
ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com
- **Information department:** Product Safety Department
- **Emergency telephone number:**
United States: 1-800-424-9300
International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**
2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate
dimethylbenzyl hydroperoxide

- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash thoroughly after handling.

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 1)

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	40 – 49%
CAS: 9004-36-8	Cellulose Acetate Butyrate Combustible Dust	5 – 9%
CAS: 80-15-9	dimethylbenzyl hydroperoxide Self-react. F, H242; Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335; Flam. Liq. 4, H227	1 – 4%
CAS: 613-48-9	N,N-Diethyl-P-Toluidine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	≤ 1%
CAS: 13463-67-7	titanium dioxide Carc. 2, H351	≤ 1%
CAS: 609-72-3	N,N-dimethyl-o-toluidine Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Flam. Liq. 4, H227	≤ 1%
CAS: 98-82-8	cumene Flam. Liq. 3, H226; Carc. 2, H351; Asp. Tox. 1, H304; Acute Tox. 4, H302; STOT SE 3, H335	≤ 1%

4 First-aid measures

- Description of first aid measures**- After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 2)

- Advice for firefighters**- Protective equipment:**

- Wear self-contained respiratory protective device.
- Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.**- Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:**- Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.**- Conditions for safe storage, including any incompatibilities****- Storage:****- Requirements to be met by storerooms and receptacles:** No special requirements.**- Information about storage in one common storage facility:** Not required.**- Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.**- Control parameters****- Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

CAS: 80-15-9 dimethylbenzyl hydroperoxide

WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

CAS: 98-82-8 cumene

PEL	Long-term value: 245 mg/m ³ , 50 ppm
	Skin

REL	Long-term value: 245 mg/m ³ , 50 ppm
	Skin

TLV	Long-term value: 5 ppm
	A3

- Additional information: The lists that were valid during the creation were used as basis.**- Exposure controls****- Personal protective equipment:****- General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 3)

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Required use of safety glasses**- Body protection:** Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties**- General Information****- Appearance:****- Form:**

Viscous

- Color:

White

- Odor:

Characteristic

- Odor threshold:

Not determined.

- pH-value:

Not determined.

- Change in condition**- Melting point/Melting range:**

Undetermined.

- Boiling point/Boiling range:

≥ 200 °C (≥ 392 °F)

- Flash point:

131 °C (267.8 °F)

- Flammability (solid, gaseous):

Not applicable.

- Decomposition temperature:

Not determined.

- Auto igniting:

Product is not selfigniting.

- Danger of explosion:

Product does not present an explosion hazard.

- Explosion limits:**- Lower:**

Not determined.

- Upper:

Not determined.

- Vapor pressure at 20 °C (68 °F):

≤ 53 hPa (≤ 39.8 mm Hg)

- Density:

Not determined.

- Relative density

Not determined.

- Vapor density

Not determined.

- Evaporation rate

Not determined.

- Solubility in / Miscibility with**- Water:**

Not miscible or difficult to mix.

- Partition coefficient (n-octanol/water): Not determined.**- Viscosity:****- Dynamic:**

Not determined.

- Kinematic:

Not determined.

- Solvent content:**- Organic solvents:**

0.8 %

- Water:

0.1 %

- VOC content:

0.75 %

7.5 g/l / 0.06 lb/gal

- Solids content:

64.1 %

- Other information

No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 4)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	6,619 mg/kg
Dermal	LD50	14,332 mg/kg
Inhalative	LC50/4 h	277 mg/l

CAS: 9004-36-8 Cellulose Acetate Butyrate

Oral	LD50	> 6,400 mg/kg (rabbit)
Dermal	LD50	> 1,000 mg/kg (rabbit)

CAS: 80-15-9 dimethylbenzyl hydroperoxide

Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)

CAS: 613-48-9 N,N-Diethyl-P-Toluidine

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

CAS: 13463-67-7 titanium dioxide

Oral	LD50	> 20,000 mg/kg (rat)
Dermal	LD50	> 10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6.82 mg/l (rat)

CAS: 609-72-3 N,N-dimethyl-o-toluidine

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

CAS: 98-82-8 cumene

Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- Sensitization:

No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

CAS: 9002-84-0	Polytetrafluoroethylene	3
CAS: 13463-67-7	titanium dioxide	2B
CAS: 98-82-8	cumene	2B
CAS: 111-76-2	2-butoxyethanol	3

- NTP (National Toxicology Program)

CAS: 98-82-8	cumene	R
CAS: 130-15-4	1,4-naphthoquinone	R

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 5)

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
 - **General notes:**
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| <ul style="list-style-type: none"> - UN-Number <li style="padding-left: 20px;">- DOT, ADN, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> - UN proper shipping name <li style="padding-left: 20px;">- DOT, ADN, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> - Transport hazard class(es) <li style="padding-left: 20px;">- DOT, ADN, IMDG, IATA <li style="padding-left: 40px;">- Class | not regulated |
| <ul style="list-style-type: none"> - Packing group <li style="padding-left: 20px;">- DOT, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> - Environmental hazards: <li style="padding-left: 20px;">- Marine pollutant: | No |
| <ul style="list-style-type: none"> - Special precautions for user | Not applicable. |
| <ul style="list-style-type: none"> - Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> - UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

CAS: 80-15-9	dimethylbenzyl hydroperoxide
CAS: 98-82-8	cumene
CAS: 111-76-2	2-butoxyethanol

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 6)

- Hazardous Air Pollutants		
CAS: 98-82-8	cumene	
CAS: 130-15-4	1,4-naphthoquinone	
- Proposition 65		
- Chemicals known to cause cancer:		
CAS: 98-82-8	cumene	
- Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
- Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
- Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
- Carcinogenic categories		
- EPA (Environmental Protection Agency)		
CAS: 98-82-8	cumene	D, CBD
CAS: 111-76-2	2-butoxyethanol	NL
- TLV (Threshold Limit Value)		
CAS: 13463-67-7	titanium dioxide	A4
CAS: 111-76-2	2-butoxyethanol	A3
- NIOSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 13463-67-7	titanium dioxide	
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affairs

- Contact: Safety, Health and Environmental Affairs

- Classification System:

- HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = *2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- NFPA ratings (scale 0 - 4)

2	1	0	Health = 2
			Fire = 1
			Reactivity = 0

- Date of preparation / last revision 07/23/2021 / 82

- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Liq. 4: Flammable liquids – Category 4
 Self-react. F: Self-reactive substances and mixtures – Type E/F
 Org. Perox. E: Organic peroxides – Type E/F
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/23/2021

Reviewed on 07/23/2021

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 7)

Asp. Tox. 1: Aspiration hazard – Category 1

- * Data compared to the previous version altered.**- Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,

®Vibra-TITE is a registered trademark of ND Industries, Inc.