

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

1 Identification**- Product identifier****- Trade name:** Vibra-TITE® Thread Sealant**- Synonyms:** Non-curing Thread Sealant**- Part number:** VT481**- Application of the substance / the mixture**
Sealing
Sealant**- Details of the supplier of the safety data sheet****- Manufacturer/Supplier:**ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com**- Information department:** Product Safety Department**- Emergency telephone number:**United States: 1-800-424-9300
International: +1-703-527-3887**2 Hazard(s) identification****- Classification of the substance or mixture**

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements**- GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**- Hazard pictograms**

GHS02 GHS07 GHS08

- Signal word Danger**- Hazard-determining components of labeling:**Soapstone
Rosin, Polymer with isophthalic acid and pentaerythritol
titanium dioxide**- Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 1)

- Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P280 Wear protective gloves.
 P280 Wear eye protection / face protection.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P321 Specific treatment (see on this label).
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 14807-96-6	Soapstone Carc. 1A, H350; STOT RE 1, H372	30 – 39%
CAS: 68515-02-6	Rosin, Polymer with isophthalic acid and pentaerythritol Skin Sens. 1B, H317; Eye Irrit. 2B, H320; Combustible Dust	20 – 29%
CAS: 67-63-0	isopropanol Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336	10 – 19%
CAS: 112-80-1	Oleic acid Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	10 – 19%
CAS: 63148-65-2	Binding agent Combustible Dust	1 – 4%
CAS: 13463-67-7	titanium dioxide Carc. 2, H351	1 – 4%

4 First-aid measures

- Description of first aid measures**- After inhalation:**

Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
 Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**- Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 2)

- Advice for firefighters

- Protective equipment:

- Wear self-contained respiratory protective device.
- Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Wear protective clothing.

- Environmental precautions:

- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

- Ensure adequate ventilation.
- Dispose of the collected material according to regulations.

- Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.

- Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:

- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

- Specific end use(s) No further relevant information available.

* 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters

- Components with limit values that require monitoring at the workplace:

- The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
- At this time, the other constituents have no known exposure limits.

CAS: 67-63-0 isopropanol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

- Ingredients with biological limit values:

CAS: 67-63-0 isopropanol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 3)

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties**- General Information****- Appearance:****- Form:**

Fluid

- Color:

According to product specification

- Odor:

Characteristic

- Odor threshold:

Not determined.

- pH-value:

Not determined.

- Change in condition**- Melting point/Melting range:**

Undetermined.

- Boiling point/Boiling range:

≥ 82 °C (≥ 179.6 °F)

- Flash point:

≥ 13 °C (≥ 55.4 °F)

- Flammability (solid, gaseous):

Not applicable.

- Ignition temperature:

> 200 °C (> 392 °F)

- Decomposition temperature:

Not determined.

- Auto igniting:

Product is not selfigniting.

- Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- Explosion limits:**- Lower:**

≥ 2 Vol %

- Upper:

≤ 12 Vol %

- Vapor pressure at 20 °C (68 °F):

≤ 43 hPa (≤ 32.3 mm Hg)

- Density:

Not determined.

- Relative density

Not determined.

- Vapor density

Not determined.

- Evaporation rate

Not determined.

- Solubility in / Miscibility with**- Water:**

Fully miscible.

- Partition coefficient (n-octanol/water): Not determined.**- Viscosity:****- Dynamic:**

Not determined.

- Kinematic:

Not determined.

- Solvent content:**- Organic solvents:**

19.0 %

- Water:

0.1 %

- VOC content:

19.00 %

190.0 g/l / 1.59 lb/gal

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 4)

- Solids content:	66.9 %
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative	LC50/4 h	158 mg/l (rat)
------------	----------	----------------

CAS: 67-63-0 isopropanol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

CAS: 112-80-1 Oleic acid

Oral	LD50	74,000 mg/kg (rat)
------	------	--------------------

CAS: 13463-67-7 titanium dioxide

Oral	LD50	> 20,000 mg/kg (rat)
Dermal	LD50	> 10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6.82 mg/l (rat)

- Primary irritant effect:

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

CAS: 14807-96-6	Soapstone	3
CAS: 67-63-0	isopropanol	3
CAS: 13463-67-7	titanium dioxide	2B

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
 - **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant



(Contd. of page 5)

- **vPvB:** Not applicable.- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.- **Uncleaned packagings:**- **Recommendation:** Disposal must be made according to official regulations.- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- UN-Number - DOT, IMDG, IATA	UN1139
- UN proper shipping name - DOT - IMDG, IATA	Coating solution COATING SOLUTION
- Transport hazard class(es) - DOT	
	
- Class - Label	3 Flammable liquids 3
- IMDG, IATA	
	
- Class - Label	3 Flammable liquids 3
- Packing group - DOT, IMDG, IATA	II
- Environmental hazards:	Not applicable.
- Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category	Warning: Flammable liquids 33 F-E,S-D B
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- Transport/Additional information: - DOT - Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**- **Sara**- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 6)

- Section 313 (Specific toxic chemical listings):		
CAS: 67-63-0	isopropanol	
- TSCA (Toxic Substances Control Act):		
All components have the value ACTIVE.		
- Hazardous Air Pollutants		
None of the ingredients is listed.		
- Proposition 65		
- Chemicals known to cause cancer:		
None of the ingredients is listed.		
- Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
- Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
- Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
- Carcinogenic categories		
- EPA (Environmental Protection Agency)		
None of the ingredients is listed.		
- TLV (Threshold Limit Value established by ACGIH)		
CAS: 14807-96-6	Soapstone	A4
CAS: 67-63-0	isopropanol	A4
CAS: 13463-67-7	titanium dioxide	A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 13463-67-7	titanium dioxide	
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs
- **Contact:** Safety, Health and Environmental Affairs
- **Classification System:**

- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **NFPA ratings (scale 0 - 4)**

3	2	0	Health = 2
			Fire = 3
			Reactivity = 0

- **Date of preparation / last revision** 11/20/2020 / 7

- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1B: Skin sensitisation – Category 1B

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 11/20/2020

Reviewed on 08/24/2020

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 7)

Carc. 1A: Carcinogenicity – Category 1A
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

- * **Data compared to the previous version altered.**

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

©ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
©Vibra-TITE is a registered trademark of ND Industries, Inc.