



Product Description

Vibra-Tite 906 is a unique anti-seize compound composed of a blend of non-metallic antifriction materials specially formulated for marine or offshore environments. This mixture of MoS₂ and complex base grease bond to metal surfaces, fill voids and imperfections on the surface shielding sliding components from interference making assembly and disassembly easy without damage to the nut or bolt.

Typical Applications

906 Anti-Seize is recommended for the following applications:

- Boiler covers
- Release paste for raised face gaskets
- Heat exchanger bolts
- Door track lubricant for sliding doors
- Centrifugal pump shaft lubricant
- Bolt lubricant for engine assembly
- Anything needing lubrication for threaded fasteners

Instructions for Use

Using the brush top applicator, apply 906 liberally to the fastener parts to be joined.

Product Characteristics

Color.....	Beige
Penetration (ASTM D-217)	285-315
Density (lb/gal)	8.9
Specific Gravity	1.07
Flash Point (ASTM D-92)	>430°F(221°C)
4-Ball (ASTM D-2596)	
Weld Point, kg	315
Load Wear Index	54.24
Wear Scar (ASTM D-2266).....	1.025
Dropping Point.....	450°F(232°C)
(ASTM D-566)	
Thickener Type	Complex Blend
Base Oil Type	Petroleum
Copper Strip Corrosion.....	1B
(ASTM D-4048)	
Water Spray-Off Resistance.....	<40%
(ASTM D-4049)	
VOC (EPA624).....	None

General Information

Shelf Life

Five years from date of manufacture.

Note

The data are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is recommended that the product be tested in the application for which it is to be used.