



Product Description

Vibra-TITE 9072 Nickel Anti-Seize paste is a high temperature resistant anti-seize paste that lubricates during assembly, providing protection against seizing, galling and excessive wear even in the most adverse conditions.

Typical Applications

This versatile lubricant can be used on construction equipment, in the marine, aircraft, oil field, farm, mining, milling industries for general plant maintenance.

Instructions for Use

Ensure parts are clean and dry.

Procedure for Application

Product is normally brushed onto components, which provides instant protection.

Properties

9072 is a heavy-duty anti-seize and lubricating paste containing a balanced blend of pure nickel and graphite, homogenized into a non-melting grease base. It does not contain any sulfur, lead, copper, halogens or clay fillers. It is a high temperature lubricant that provides maximum protection against corrosion even with temperatures exceeding 2000 °F.

Technical Features

Base..... Synthetic Oils and lubricants
Color:.....Silver
Viscosity (Thixotropic)...500K-350K (paste)
Shelf Life..... 5 years @ 68°F
Max. Operating Temp..... -65°F to +2600°F

Performance Data

Lubricity (K Factor).....0.13
Coefficient of Friction.....0.17 @ 161°F
Meets Mil Spec..... MIL-A-907E

General Information

Storage

Product should be stored in a cool and dry location at temperatures between -10 °C to 30 °C. Optimal storage is 22±4°C. Shelf life is 5 years from date of manufacture when stored at 22±4°C.

Note

Nickel is a hard metal that keeps surfaces apart. It is particularly well suited for applications that involve the use of different metals (such as brass to steel). Product conforms to MIL-A-907E / MIL-PRF-907E.

Health & Safety in use

Because of solid content, use of gloves and goggles are recommended.