05/03/2019	Kit Components
Product code	Description
VTPB422 Vibra-TITE® Methacrylate Adhesives PB422 Medium Set Time - Structural	
Components:	
VTPB422A	Vibra-TITE® Methacrylate Adhesives PB422 Medium Set Time - Structural - Part A
VTPB422B	Vibra-TITE® Methacrylate Adhesives PB422 Medium Set Time - Structural - Part B





Printing date 05/03/2019 Reviewed on 04/16/2019

1 Identification

- Product identifier
 - Trade name: Vibra-TITE® Methacrylate Adhesives
 - Synonyms: PB422 Medium Set Time Structural Part A
 - Part number: VTPB422A
 - Application of the substance / the mixture Adhesives
- Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017

USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department
- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- Label elements
 - GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms









GHS02 GHS05 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling:

methyl methacrylate Methacrylic acid

Rosin

Monofunctional acid ester

- Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 1)

H351 Suspected of causing cancer. H335 May cause respiratory irritation.

- Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P242 Use only non-sparking tools.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304+P340

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label). P312 Call a poison center/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information:

2 % of the mixture consists of component(s) of unknown toxicity.

- Classification system:

- NFPA ratings (scale 0 - 4)



Reactivity = 0

- HMIS-ratings (scale 0 - 4)



- Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous	components:	
CAS: 80-62-6	methyl methacrylate	70 – 79%
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 79-41-4	Methacrylic acid	1 – 4%
	Acute Tox. 3, H311; Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335; Flam. Liq. 4, H227	
CAS: 41637-38-1	Ethoxylated Bisphenol A Dimethacrylate Esters	1 – 4%
	Eye Irrit. 2A, H319	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	≤ 1%
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Carc. 2, H351; STOT RE 2, H373; Flam. Liq. 4, H227	
CAS: 8050-09-7	Rosin	≤ 1%
	Skin Sens. 1, H317	
	Monofunctional acid ester	≤ 1%
	Acute Tox. 3, H311; Skin Corr. 1C, H314; Eye Dam. 1, H318; Skin Sens. 1, H317	

4 First-aid measures

- Description of first aid measures

- After inhalation:

Supply fresh air and to be sure call for a doctor.

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

CO2, sand, extinguishing powder. Do not use water.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: Store in a cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

CAS: 80-62-6 methyl methacrylate

PEL Long-term value: 410 mg/m³, 100 ppm

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

	(Contd. of page 3)
REL	Long-term value: 410 mg/m³, 100 ppm
TLV	Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm DSEN
CAS:	79-41-4 Methacrylic acid
REL	Long-term value: 70 mg/m³, 20 ppm Skin
TLV	Long-term value: 70 mg/m³, 20 ppm
CAS:	99-97-8 N,N-dimethyl-p-toluidine
WEEL	Long-term value: 0.5 ppm
CAS:	8050-09-7 Rosin
TLV	DSEN, RSEN, L
	A LUCY II A CONTROL OF THE CONTROL O

⁻ Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and che - General Information - Appearance:	mical properties
- Form:	Viscous
- Color:	Whitish
- Odor:	Pungent
- Odor threshold:	Not determined.
- pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. ≥ 101 °C (≥ 213.8 °F)
- Flash point:	10 °C (50 °F)
- Flammability (solid, gaseous):	Not applicable.
- Ignition temperature:	430 °C (806 °F)
- Decomposition temperature:	Not determined.

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 4)

- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- Explosion limits:	
- Lower:	2.1 Vol %
- Upper:	12.5 Vol %
- Vapor pressure at 20 °C (68 °F):	≤ 47 hPa (≤ 35.3 mm Hg)
- Density:	Not determined.
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/wa	ter): Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic at 20 °C (68 °F):	180,000 mm²/s
- Solvent content:	
Organic solvents:	0.2 %
- Water:	0.0 %
- VOC content:	0.16 %
	1.6 g/l / 0.01 lb/gal
- Solids content:	23.2 %
Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
 - Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

*11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:

		alues that are relevant for classification:
•		y Estimate)
Oral	LD50	11,796 mg/kg
Dermal	LD50	10,791 mg/kg
Inhalative	LC50/4 h	200 mg/l
CAS: 80-6	2-6 methy	vl methacrylate
Oral	LD50	7,872 mg/kg (rat)
CAS: 79-4	1-4 Metha	crylic acid
Oral	LD50	1,332 mg/kg (mouse)
Dermal	LD50	500 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
CAS: 99-9	7-8 N,N-d	imethyl-p-toluidine
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)
Monofund	tional aci	d ester
Dermal	LD50	300 mg/kg (ATE)
		(Contd. on page

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 5)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

- IARO	C (International Agency for Research on Cancer)	
CAS: 80-62-6	methyl methacrylate	3
CAS: 9010-98-4	Neoprene rubber	3
CAS: 99-97-8	N,N-dimethyl-p-toluidine	2B
CAS: 14807-96-6	Soapstone	3
- NTP	(National Toxicology Program)	
CAS: 130-15-4 1	,4-naphthoquinone	R
- OSH	A-Ca (Occupational Safety & Health Administration)	
None of the ingre	dients is listed.	

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:
 - Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number
 - DOT, IMDG, IATA

UN1133

3 Flammable liquids

- UN proper shipping name

- DOT

Adhesives - IMDG, IATA **ADHESIVES**

- Transport hazard class(es)

- DOT



- Class

- Label 3

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 6)

(Contd. on page 8)

- IMDG, IATA - Class 3 Flammable liquids - Label - Packing group - DOT, IMDG, IATA Ш Not applicable. - Environmental hazards: - Special precautions for user Warning: Flammable liquids - Danger code (Kemler): - EMS Number: F-E,S-D - Stowage Category Α - Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. - Transport/Additional information: - DOT Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L - IMDG - Limited quantities (LQ) 5L - Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml - UN "Model Regulation": UN 1133 ADHESIVES, 3, III

*15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture - Sara

- Section 3	55 (extremely hazardous substances):	
None of the ingredients	is listed.	
- Section 3	13 (Specific toxic chemical listings):	
CAS: 80-62-6 methyl n	nethacrylate	
Monofur	ctional acid ester	
- TSCA (Toxic	Substances Control Act):	
methyl methacrylate		ACTIVI
Impact modifying resin		ACTIV
Neoprene rubber		ACTIV
Methacrylic acid		ACTIV
Acrylic Resin		ACTIV
<u> </u>	A Dimethacrylate Esters	ACTIV
Wax		ACTIV
N,N-dimethyl-p-toluidin	•	ACTIV
Rosin		ACTIV
Monofunctional acid es	er	* ACTIV
	propane-1,2-diol	
Polymerization inhibitor		ACTIV
Soapstone		ACTIVI
1,4-naphthoquinone		ACTIV
tetrasodium ethylenediaminetetraacetate		ACTIV
Deionized water		ACTIV
- Hazardou	s Air Pollutants	
CAS: 80-62-6 methyl	methacrylate	
CAS: 130-15-4 1,4-nap	hthoquinone	

Printing date 05/03/2019 Reviewed on 04/16/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

- Proposition 65

(Contd. of page 7)

- Chen	- Chemicals known to cause cancer:	
	Impact modifying resin	
CAS: 41637-38-1	Ethoxylated Bisphenol A Dimethacrylate Esters	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	
- Chen	nicals known to cause reproductive toxicity for females:	
Impact modifying	resin	
Monofunctional ac	Monofunctional acid ester	
- Chen	nicals known to cause reproductive toxicity for males:	
Impact modifying	Impact modifying resin	
Monofunctional ac	Monofunctional acid ester	
- Chen	nicals known to cause developmental toxicity:	
Monofunctional ac	Monofunctional acid ester	

- Carcinogenic categories

- EPA (Environmental Protection Agency)	
CAS: 80-62-6 methyl methacrylate	E, NL
- TLV (Threshold Limit Value established by ACGIH)	
CAS: 80-62-6 methyl methacrylate	A4
CAS: 14807-96-6 Soapstone	A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
 - Date of preparation / last revision 05/03/2019 / 16
 - Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation
IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* Data compared to the previous version altered.

Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.





Printing date 05/03/2019 Reviewed on 05/03/2019

1 Identification

- Product identifier

- Trade name: Vibra-TITE® Methacrylate Adhesives

- Synonyms: PB422 Medium Set Time - Structural - Part B

- Part number: VTPB422B

- Application of the substance / the mixture Adhesives

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017

USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department

- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



Harmful if swallowed. Acute Tox. 4 H302 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Flam. Liq. 4 H227 Combustible liquid.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





- Signal word Warning

- Hazard-determining components of labeling:

Bisphenol-A epoxy resin dimethylbenzyl hydroperoxide benzoyl peroxyde zinc distearate

- Hazard statements

H227 Combustible liquid. H302 Harmful if swallowed. H315 Causes skin irritation. Causes serious eye irritation. H319 H317 May cause an allergic skin reaction. Suspected of causing cancer. H351

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from flames and hot surfaces. - No smoking.

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

P261 Avoid breathing dust/fume/gas/mist/vapors/spray P264 Wash face, hands and any exposed skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P280 Wear protective gloves. P280 Wear eye protection / face protection. P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. P330 Rinse mouth. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P321 Specific treatment (see on this label).

P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233

Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:

- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous c	components:	
CAS: 25068-38-6	Bisphenol-A epoxy resin	50 – 59%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 94-36-0	benzoyl peroxyde	20 – 29%
	Org. Perox. B, H241; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
CAS: 131298-44-7	branched C10-alkyl benzoates	5 – 9%
	Acute Tox. 4, H332	
CAS: 1317-65-3	Calcium Carbonate	5 – 9%
	Skin Irrit. 2, H315	
CAS: 80-15-9	dimethylbenzyl hydroperoxide	1 – 4%
	Self-react. F, H242; Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335; Flam. Liq. 4, H227	
CAS: 67762-90-7	Amorphous Silica	1 – 4%
	Combustible Dust	
CAS: 557-05-1	zinc distearate	1 – 4%
	STOT SE 3, H335	
CAS: 98-82-8	cumene	≤ 1%
	Flam. Liq. 3, H226; Carc. 2, H351; Asp. Tox. 1, H304; Acute Tox. 4, H302; STOT SE 3, H335	

4 First-aid measures

- Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 2)

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Immediately call a doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

CO2, sand, extinguishing powder. Do not use water.

- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective clothing.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Protect from heat.
- Conditions for safe storage, including any incompatibilities
 - Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 3)

80-15-9 dimethylbenzyl hydroperoxide
Long-term value: 6 mg/m³, 1 ppm Skin
69012-64-2 Silica-Amorphous Silica fume
TLV withdrawn
557-05-1 zinc distearate
Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
Long-term value: 10 mg/m³
98-82-8 cumene
Long-term value: 245 mg/m³, 50 ppm Skin
Long-term value: 245 mg/m³, 50 ppm Skin
Long-term value: (246) NIC-0.5 mg/m³, (50) NIC-0.1 ppm NIC-A3

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eve protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Viscous
Color: Whitish
Odor: Pungent
Odor threshold: Not determined.

- **pH-value:** Not determined.

- Change in condition

- Melting point/Melting range: Undetermined.
- Boiling point/Boiling range: ≥ 260 °C (≥ 500 °F)

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 4)

- Flash point:	84 °C (183.2 °F)
- Flammability (solid, gaseous):	Not applicable.
- Decomposition temperature.	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Not determined.
- Explosion limits:	
- Lower:	Not determined.
- Upper:	Not determined.
- Vapor pressure:	Not determined.
- Density at 20 °C (68 °F):	~ 0.96 g/cm³ (~ 8.0112 lbs/gal)
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
•	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/	water): Not determined.
- Viscosity:	
- Dynamic at 20 °C (68 °F):	80,000 mPas
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	0.3 %
- VOC content:	0.30 %
	~ 2.9 g/l / ~ 0.02 lb/gal
- Solids content:	7.2 %
- Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
 - Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

*11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:

- LL	D/LC50 v	alues that are relevant for classification:
ATE (Acut	te Toxicity	r Estimate)
Oral	LD50	15,159 mg/kg (rat)
Dermal	LD50	19,841 mg/kg (rat)
Inhalative	LC50/4 h	135 mg/l
CAS: 1312	298-44-7 b	ranched C10-alkyl benzoates
Inhalative	LC50/4 h	11 mg/l (ATE)
CAS: 80-1	5-9 dimet	hylbenzyl hydroperoxide
Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)
CAS: 557-	05-1 zinc	distearate
Oral	LD50	10,000 mg/kg (rat)
CAS: 98-8	2-8 cume	ne
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

Inhalative LC50/4 h 24.7 mg/l (mouse)

(Contd. of page 5)

- Primary irritant effect:

- - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful Irritant

- Carcinogenic categories

- IARC	(International Agency for Research on Cancer)	
CAS: 94-36-0	benzoyl peroxyde	3
CAS: 69012-64-2	Silica-Amorphous Silica fume	3
CAS: 98-82-8	cumene	2B
CAS: 128-37-0	Butylated hydroxytoluene	3
- NTP	(National Toxicology Program)	
CAS: 98-82-8 cur	nene	R
- OSHA	A-Ca (Occupational Safety & Health Administration)	
None of the ingred	lients is listed.	

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Ecotoxical effects:
 - Remark: Toxic for fish

- Additional ecological information:

- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment

- PBT: Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number - DOT - IMDG, IATA	not regulated UN3082
- UN proper shipping name - DOT - IMDG	not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN, dimethylbenzyl hydroperoxide),
- IATA	MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN)

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 6)

- Transport hazard class(es)	
- DOT	
- DOT - Class	not regulated
- IMDG, IATA	
- Class	9 Miscellaneous dangerous substances and articles
- Label	9
- Packing group	
- DOT	not regulated
- IMDG, IATA	III
- Environmental hazards:	Product contains environmentally hazardous substances: LIQUID EPOXY RESIN
- Marine pollutant:	Yes Symbol (fish and tree)
- Special marking (IATA):	Symbol (fish and tree)
- Special precautions for user	Warning: Miscellaneous dangerous substances and articles
- Danger code (Kemler):	90
- EMS Number:	F-A,S-F
- Stowage Category	A
- Transport in bulk according to Annex II of MARP	OL73/78
and the IBC Code	Not applicable.
- Transport/Additional information:	
- IMDG	
 Limited quantities (LQ) 	5L
- Excepted quantities (ÉQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN), 9, III

*15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Sara	
- Sect	tion 355 (extremely hazardous substances):
None of the ingre	edients is listed.
- Sect	tion 313 (Specific toxic chemical listings):
CAS: 94-36-0 b	penzoyl peroxyde
CAS: 80-15-9	limethylbenzyl hydroperoxide
CAS: 557-05-1 z	rinc distearate
CAS: 98-82-8	cumene
- TSCA (Toxic Substances Control Act):
All components h	nave the value ACTIVE.
- Haza	ardous Air Pollutants
CAS: 98-82-8 cu	imene
- Propos	ition 65
- Che	micals known to cause cancer:

- Chemicals known to cause cancer:

CAS: 98-82-8 | cumene

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 8)

Printing date 05/03/2019 Reviewed on 05/03/2019

Trade name: Vibra-TITE® Methacrylate Adhesives

(Contd. of page 7) - Chemicals known to cause developmental toxicity: None of the ingredients is listed.

- Carcinogenic categories

- <i>EP</i>	A (Environmental Protection Agency)		
CAS: 557-05-1	zinc distearate	D,	I, II
CAS: 98-82-8	cumene	D,	CBD
- TL	V (Threshold Limit Value established by ACGIH)		
CAS: 94-36-0	benzoyl peroxyde		A4
CAS: 128-37-0	Butylated hydroxytoluene		A4
- NIC	OSH-Ca (National Institute for Occupational Safety and Health)		
None of the ing	redients is listed.		

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
 - Date of preparation / last revision 05/03/2019 / 13

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation
IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

REL: Recommended Exposure Limit
Flam. Liq. 3: Flammable liquids — Category 3
Flam. Liq. 4: Flammable liquids — Category 4
Self-react. F: Self-reactive substances and mixtures — Type E/F
Org. Perox. B: Organic peroxides — Type B
Org. Perox. E: Organic peroxides — Type E/F
Acute Tox. 3: Acute toxicity — Category 3
Acute Tox. 4: Acute toxicity — Category 4
Skin Corr. 1B: Skin corrosion/irritation — Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.