

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

1 Identification

- Product identifier

- **Trade name:** Vibra-TITE® Threadlocker
- **Synonyms:** 140 High Strength Threadlocker
- **Part number:** VT140

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**
ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com

- **Information department:** Product safety department

- **Emergency telephone number:**

United States: 1-800-424-9300
International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

2-hydroxyethyl methacrylate
Polyglycol dimethacrylate
dimethylbenzyl hydroperoxide

- **Hazard statements**

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash face, hands and any exposed skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 1)

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a poison center/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information:

8.5 % of the mixture consists of component(s) of unknown toxicity.

- Classification system:**- NFPA ratings (scale 0 - 4)**

2	1	0
Health = 2	Fire = 1	Reactivity = 0

- HMIS-ratings (scale 0 - 4)

HEALTH 2	Health = *2
FIRE 1	Fire = 1
REACTIVITY 0	Reactivity = 0

- Other hazards**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- Chemical characterization: Mixtures- **Description:** Mixture of the substances listed below with nonhazardous additions.**- Dangerous components:**

25852-47-5	Polyglycol dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	30-39%
868-77-9	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	20-29%
39382-25-7	Bisphenol-A Fumarate Resin Skin Irrit. 2, H315; Eye Irrit. 2B, H320	20-29%
41637-38-1	Ethoxylated Bisphenol A Dimethacrylate Esters Skin Irrit. 2, H315; Eye Irrit. 2A, H319	5-9%
	Modified Epoxy Acrylate Oligomer Skin Irrit. 2, H315; Flam. Liq. 4, H227; Eye Irrit. 2B, H320	1-4%
80-15-9	dimethylbenzyl hydroperoxide Self-react. F, H242; Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335; Flam. Liq. 4, H227	1-4%
128-44-9	Saccharin Acute Tox. 4, H302; Combustible Dust	1-4%
57-55-6	Propylene glycol Acute Tox. 4, H302	1-4%

4 First-aid measures

- Description of first aid measures**- After inhalation:**

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.- **After swallowing:** If symptoms persist consult doctor.**- Information for doctor:**- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
CO₂, sand, extinguishing powder. Do not use water.
 - **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Wear protective clothing.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
No special precautions are necessary if used correctly.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

80-15-9 dimethylbenzyl hydroperoxide	
WEEL	Long-term value: 6 mg/m ³ , 1 ppm Skin
57-55-6 Propylene glycol	
WEEL	Long-term value: 10 mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 3)

- Exposure controls**- Personal protective equipment:****- General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:

Tightly sealed goggles

- Body protection: Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties**- General Information****- Appearance:**

- Form:	Fluid
- Color:	Red
- Odor:	Characteristic
- Odor threshold:	Not determined.

- pH-value:	Not determined.
--------------------	-----------------

- Change in condition

- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	>195 °C (>383 °F)

- Flash point:	94 °C (201.2 °F)
-----------------------	------------------

- Flammability (solid, gaseous):	Not applicable.
---	-----------------

- Ignition temperature:	n.a. °C
--------------------------------	---------

- Decomposition temperature:	Not determined.
-------------------------------------	-----------------

- Auto igniting:	Product is not selfigniting.
-------------------------	------------------------------

- Danger of explosion:	Product does not present an explosion hazard.
-------------------------------	---

- Explosion limits:

- Lower:	Not determined.
- Upper:	Not determined.

- Vapor pressure at 68 °C (154.4 °F):	≤1.3 hPa (≤1 mm Hg)
--	---------------------

- Density at 20 °C (68 °F):	~1.1 g/cm ³ (~9.1795 lbs/gal)
------------------------------------	--

- Relative density	Not determined.
---------------------------	-----------------

- Vapor density	Not determined.
------------------------	-----------------

- Evaporation rate	Not determined.
---------------------------	-----------------

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 4)

- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water): Not determined.	
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	1.4 %
- Water:	1.4 %
- VOC content:	1.37 % ~15.1 g/l / ~0.13 lb/gl
- Solids content:	32.3 %
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
 - Aldehyde
 - Hydrocarbons

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

- LD/LC50 values that are relevant for classification:		
868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5,050 mg/kg (rat)
80-15-9 dimethylbenzyl hydroperoxide		
Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)
128-44-9 Saccharin		
Oral	LD50	1,280 mg/kg (rat)
57-55-6 Propylene glycol		
Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
- NTP (National Toxicology Program)	
130-15-4	1,4-naphthoquinone R
- OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 5)

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
 - **General notes:**
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- UN-Number	
- DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name	
- DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA	
- Class	not regulated
- Packing group	
- DOT, IMDG, IATA	not regulated
- Environmental hazards:	
- Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- UN "Model Regulation":	not regulated

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

80-15-9 dimethylbenzyl hydroperoxide

- TSCA (Toxic Substances Control Act):

Polyglycol dimethacrylate
 2-hydroxyethyl methacrylate
 Bisphenol-A Fumarate Resin
 Ethoxylated Bisphenol A Dimethacrylate Esters
 dimethylbenzyl hydroperoxide
 Saccharin
 Propylene glycol

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 6)

2'-phenylacetohydrazide
N-isopropylhydroxylamine
1-hydroxyethane-1,1-diybis(phosphonic acid)
1,4-naphthoquinone
phosphorous acid
acetone oxime
Deionized water

- TSCA new (21st Century Act) (Substances not listed)

25852-47-5	Polyglycol dimethacrylate
39382-25-7	Bisphenol-A Fumarate Resin
41637-38-1	Ethoxylated Bisphenol A Dimethacrylate Esters
	Modified Epoxy Acrylate Oligomer

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affairs

- Contact: Safety, Health and Environmental Affairs

- Date of preparation / last revision 01/31/2018 / 29

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 4: Flammable liquids – Category 4
 Self-react. F: Self-reactive substances and mixtures – Type E/F
 Org. Perox. E: Organic peroxides – Type E/F
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/31/2018

Reviewed on 01/16/2018

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 7)

Asp. Tox. 1: Aspiration hazard – Category 1

- * Data compared to the previous version altered.**- Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

©ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,

©Vibra-TITE is a registered trademark of ND Industries, Inc.