



**Product Description**

Vibra-Tite Excel 626 Polyolefin Primer is an ozone friendly primer used to prepare polyolefin surfaces for bonding with Vibra-Tite cyanoacrylate adhesives.

**Typical Applications**

Vibra-Tite Excel 626 primer improves adhesion to low energy surfaces when bonding with cyanoacrylate adhesives.

**Procedure for Application**

Product is normally hand applied from the bottle by brushing, wiping or spraying onto parts.

**Properties**

Vibra-Tite Excel 626 primer is supplied in an ozone friendly blend of flammable solvents. Care must be taken to avoid flames.

**Technical Features**

Chemical Base ..... Acetone  
Color: ..... Clear/Amber  
Viscosity ..... <1cps  
Shelf Life ..... 12 months @ 68°F unopened  
Flammability ..... Yes, high

**Performance Attributes**

Dry Time ..... 15 -30 seconds  
On-Part Life ..... 5 minute

**Presentation**

Bottles...2 oz, 4oz, 8 oz (with pump sprayer)  
Cans ..... Gallon

**General Information**

**Storage**

Store in cool area out of direct sunlight

**Note**

Vibra-Tite Excel 626 Polyolefin Primer is used to improve adhesion to polyolefin and other low energy surfaces and is applied prior to the application of the SuperGlue.

**Health & Safety in use**

Use in well ventilated area and read MSDS.