

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

1 Identification**- Product identifier****- Trade name:** Vibra-TITE® Excel Primer**- Synonyms:** 612 Excel Primer T**- Part number:** VT612**- Relevant identified uses of the substance or mixture** Surface preparation of adhesive application**- Details of the supplier of the safety data sheet****- Manufacturer/Supplier:**ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA

Telephone: +1-248-288-0000

Email: info@ndindustries.com

Website: www.ndindustries.com

- Information department: Product safety department**- Emergency telephone number:**

United States: 1-800-424-9300

International: +1-703-527-3887

2 Hazard(s) identification**- Classification of the substance or mixture**

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements**- GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**- Hazard pictograms**

GHS02 GHS07

- Signal word Danger**- Hazard-determining components of labeling:**

heptane

acetone

propan-2-ol

- Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241

Use explosion-proof electrical/ventilating/lighting/equipment.

P261

Avoid breathing dust/fume/gas/mist/vapors/spray

P280

Wear protective gloves / eye protection / face protection.

P280

Wear protective gloves.

P280

Wear eye protection / face protection.

P240

Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 1)

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:**- NFPA ratings (scale 0 - 4)****- HMIS-ratings (scale 0 - 4)****- Other hazards****- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*** 3 Composition/information on ingredients****- Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

142-82-5	heptane	50-60%
67-64-1	acetone	20-30%
67-63-0	propan-2-ol	10-20%
	Accelerator	1-5%
99-97-8	N,N-dimethyl-p-toluidine	1-5%

*** 4 First-aid measures****- Description of first aid measures****- General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Immediately call a doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

*** 5 Fire-fighting measures****- Extinguishing media****- Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

- Advice for firefighters**- Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

Wear fully protective suit.

*** 6 Accidental release measures****- Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 2)

- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
 Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- Handling:**- Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities**- Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

* 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.**- Control parameters****- Components with limit values that require monitoring at the workplace:****142-82-5 heptane**

PEL	Long-term value: 2000 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

99-97-8 N,N-dimethyl-p-toluidine

WEEL	Long-term value: 0.5 ppm
------	--------------------------

- Ingredients with biological limit values:**67-64-1 acetone**

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 3)

- **Additional information:** The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

- **Form:** Fluid
- **Color:** Colorless
- **Odor:** Solvent-like
- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- Change in condition

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** 55 °C (131 °F)

- **Flash point:** -17 °C (1 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 215 °C (419 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- Explosion limits:

- **Lower:** 1.1 Vol %
- **Upper:** 13.0 Vol %

- **Vapor pressure at 20 °C (68 °F):** 233 hPa (175 mm Hg)

- **Density:** Not determined.

- **Relative density:** Not determined.
- **Vapour density:** Not determined.
- **Evaporation rate:** Not determined.

- Solubility in / Miscibility with

- **Water:** Not miscible or difficult to mix.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 4)

- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	94.0 %
- VOC content:	69.1 % 690.5 g/l / 5.76 lb/gal
- Solids content:	3.0 %
- Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity

- Chemical stability

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- **Incompatible materials:** No further relevant information available.

- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

Accelerator

Oral	LD50	3800 mg/kg (rat)
Dermal	LD50	7940 mg/kg (rabbit)

99-97-8 N,N-dimethyl-p-toluidine

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

67-63-0 propan-2-ol	3
---------------------	---

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 5)

- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
 - **Remark:** Very toxic for fish
- **Additional ecological information:**
 - **General notes:**
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Also poisonous for fish and plankton in water bodies.
 - Very toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

*14 Transport information

<ul style="list-style-type: none"> - UN-Number - DOT, IMDG, IATA 	UN1993	
<ul style="list-style-type: none"> - UN proper shipping name - DOT - IMDG - IATA 	Flammable liquids, n.o.s. (Heptanes, Acetone) FLAMMABLE LIQUID, N.O.S. (HEPTANES, ACETONE), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (HEPTANES, ACETONE)	
<ul style="list-style-type: none"> - Transport hazard class(es) - DOT 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> - Class - Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> - IMDG 	<div style="text-align: center;">   </div> <ul style="list-style-type: none"> - Class - Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> - IATA 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> - Class - Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> - Packing group - DOT, IMDG, IATA 	II	
<ul style="list-style-type: none"> - Environmental hazards: - Marine pollutant: 	Product contains environmentally hazardous substances: heptane Yes Symbol (fish and tree)	
<ul style="list-style-type: none"> - Special precautions for user - Danger code (Kemler): 	Warning: Flammable liquids 33	

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 6)

- EMS Number:	F-E,S-E
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- Transport/Additional information:	
- DOT	
- Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN1993, Flammable liquids, n.o.s. (Heptanes, Acetone), ENVIRONMENTALLY HAZARDOUS, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

67-63-0 propan-2-ol

- **TSCA (Toxic Substances Control Act):**

heptane

acetone

propan-2-ol

N,N-dimethyl-p-toluidine

- **Proposition 65**- **Chemicals known to cause cancer:**

99-97-8 N,N-dimethyl-p-toluidine

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**- **EPA (Environmental Protection Agency)**

142-82-5 heptane

D

67-64-1 acetone

I

- **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

67-63-0 propan-2-ol

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs

- **Contact:** Safety, Health and Environmental Affairs

- **Date of preparation / last revision** 05/01/2015 / 5

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/01/2015

Reviewed on 05/01/2015

Trade name: Vibra-TITE® Excel Primer

(Contd. of page 7)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

- * **Data compared to the previous version altered.**

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
®Vibra-TITE is a registered trademark of ND Industries, Inc.