



Page 1/7

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/29/2024 Reviewed on 01/29/2024

1 Identification

- Product identifier

- Trade name: Vibra-TITE® Threadlocker
 - Synonyms: 122 Oil Tolerant Threadlocker

- Part number: VT122

- Application of the substance / the mixture Thread Locking

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department
- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard identification

- Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity – Category 2 H351 Suspected of causing cancer.



Skin Irritation - Category 2

Eye Irritation - Category 2A

Skin Sensitizer - Category 1

Specific Target Organ Toxicity - Single Exposure - Category 3

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms





GHS07 GHS08

- Signal word Warning

- Hazard-determining components of labeling:

2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate methacrylic acid, monoester with propane-1,2-diol Cumene

2'-phenylacetohydrazide

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

- Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 1) P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P280 Wear protective gloves. P302+P352 If on skin: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. P312 P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P321 Specific treatment (see on this label). P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/Information on ingredients

- Chemical characterization: Mixtures

P501

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous	components:	
CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H335	45 – 70% w/v
CAS: 8002-74-2	Paraffin wax Combustible Dusts - Category 1	1 – 5% w/w
CAS: 27813-02-1	methacrylic acid, monoester with propane-1,2-diol Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317	1 – 5% w/w
CAS: 80-15-9	dimethylbenzyl hydroperoxide Self-reactive Substances and Mixtures – Type F, H242; Organic Peroxides – Type E, H242; Acute Toxicity (Inhalation) - Category 3, H331; Specific Target Organ Toxicity - Repeated Exposure - Category 2, H373; Aspiration Hazard - Category 1, H304; Skin Corrosion - Category 1B, H314; Serious Eye Damage - Category 1, H318; Acute Toxicity (Oral) - Category 4, H302; Acute Toxicity (Dermal) – Category 4, H312; Specific Target Organ Toxicity - Single Exposure - Category 3, H335; Flammable Liquids - Category 4, H227	0.1 – 1% w/w
CAS: 114-83-0	2'-phenylacetohydrazide Acute Toxicity (Oral) - Category 4, H302; Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317; Specific Target Organ Toxicity - Single Exposure - Category 3, H335	0.1 – 1% w/v
CAS: 98-82-8	Cumene Flammable Liquids - Category 3, H226; Carcinogenicity – Category 2, H351; Aspiration Hazard - Category 1, H304; Acute Toxicity (Oral) - Category 4, H302; Specific Target Organ Toxicity - Single Exposure - Category 3, H335	≤ 0.1% w/w

4 First-aid measures

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 - Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Threadlocker

Wear fully protective suit.

(Contd. of page 2)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special precautions are necessary if used correctly.

Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see section 7.

- Control parameters

- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

,	is, the other constituents have no known expectate limits.
CAS: 8002-74	I-2 Paraffin wax
EL (Canada)	TWA: 2 mg/m³
EV (Canada)	TWA: 2 mg/m³
	fume
REL (USA)	TWA: 2 mg/m³
TLV (USA)	TWA: 2 mg/m³
CAS: 80-15-9	dimethylbenzyl hydroperoxide
WEEL (USA)	TWA: 6 mg/m³, 1 ppm
	Skin
CAS: 98-82-8	Cumene
EL (Canada)	STEL: 75 ppm
	TWA: 25 ppm IARC 2B
E)//(0)	
EV (Canada)	TWA: 245 mg/m³, 50 ppm Skin
DEL (LICA)	
PEL (USA)	TWA: 245 mg/m³, 50 ppm Skin
REL (USA)	TWA: 245 mg/m³, 50 ppm
REL (USA)	Skin
TLV (USA)	TWA: 5 ppm
(5 5 . 1)	A3
	disconding amonding. The list that we will desire the continue of the second second

⁻ Additional information: The lists that were valid during the creation were used as basis.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 3)

- Exposure controls

- Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Required use of safety glasses
- Body protection: Protective work clothing

9 Physical and chemical properties

nformation on basic physical and che - General Information	illical properties
- Appearance:	
- Form:	Fluid
- Color:	Blue
- Odor:	Characteristic
- Odor threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
 Melting point/Melting range: 	Undetermined.
Boiling point/Boiling range:	≥ 200 °C
- Flash point:	131 °C
- Flammability (solid, gaseous):	Not applicable.
- Auto igniting:	> 300 °C
- Decomposition temperature:	Not determined.
- Ignition temperature:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits:	
- Lower:	Not determined.
- Upper:	Not determined.
- Vapor pressure:	Not determined.
- Density:	Not determined.
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 4)

- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
Organic solvents:	0.8 %
- Water:	1.4 %
- VOC content:	0.77 %
	7.7 g/l / 0.06 lb/gal
- Solids content:	78.3 %
- Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Aldehyde Hydrocarbons

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

	,		
- LI	- LD/LC50 values that are relevant for classification:		
ATE (Acut	te Toxicity	r Estimate)	
Inhalative	LC50/4 h	26,190 mg/l (rat)	
CAS: 80-1	5-9 dimet	hylbenzyl hydroperoxide	
Oral	LD50	382 mg/kg (rat)	
Dermal	LD50	500 mg/kg (rat)	
Inhalative	LC50/4 h	220 mg/l (rat)	
CAS: 114-	CAS: 114-83-0 2'-phenylacetohydrazide		
Oral	LD50	270 mg/kg (mouse)	
CAS: 98-82-8 Cumene			
Oral	LD50	1,400 mg/kg (rat)	
Dermal	LD50	12,300 mg/kg (rabbit)	
Inhalative	LC50/4 h	24.7 mg/l (mouse)	

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)			
CAS: 98-82-8	Cumene	2B	
CAS: 13463-67-7	titanium dioxide	2B	
- NTP	- NTP (National Toxicology Program)		
CAS: 98-82-8	Cumene	R	
CAS: 130-15-4	,4-naphthoquinone	R	

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Threadlocker

(Contd. of page 5)

- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

14 Transport information	
- UN-Number - DOT/TDG, ADR, ADN, IMDG, IATA	not regulated
- UN proper shipping name - DOT/TDG, ADR, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT/TDG, ADR, ADN, IMDG, IATA - Class	not regulated
- Packing group - DOT/TDG, ADR, IMDG, IATA	not regulated
- Environmental hazards: - Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of MARI and the IBC Code	POL73/78 Not applicable.
- UN "Model Regulation":	not regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 - Sara

- Se	- Section 355 (extremely hazardous substances):		
None of the in	gredients is listed.		
- Se	ection 313 (Specific toxic chemical listings):		
CAS: 80-15-9	dimethylbenzyl hydroperoxide		
CAS: 98-82-8	Cumene		
CAS: 98-86-2	acetophenone		
- TSCA	- TSCA (Toxic Substances Control Act):		
All component	All components have the value ACTIVE.		

- Canadian substance listings:

- Canadian Substance iistings.	
- Canad	dian Domestic Substances List (DSL)
CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate
CAS: 61791-29-5	Fatty Acid Ester
CAS: 68139-91-3	Polyethylene glycol diocoate
CAS: 8002-74-2	Paraffin wax
CAS: 27813-02-1	methacrylic acid, monoester with propane-1,2-diol
	Polyvinyl acetate

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Threadlocker

	(Contd. of page 6)	
CAS: 67762-90-7	Amorphous Silica	
CAS: 7732-18-5	Deionized water	
CAS: 128-44-9	Saccharin	
CAS: 80-15-9	dimethylbenzyl hydroperoxide	
CAS: 25322-68-3	Polyethylene glycol	
CAS: 61788-47-4	Coco fatty acid	
CAS: 57-55-6	propane-1,2-diol	
CAS: 114-83-0	2'-phenylacetohydrazide	
CAS: 98-82-8	Cumene	
CAS: 5080-22-8	N-isopropylhydroxylamine	
CAS: 64-02-8	tetrasodium ethylenediaminetetraacetate	
CAS: 2809-21-4	1-hydroxyethane-1,1-diylbis(phosphonic acid)	
CAS: 98-86-2	acetophenone	
CAS: 617-94-7	2-Phenyl-2-propanol	
CAS: 13463-67-7	titanium dioxide	
CAS: 130-15-4	1,4-naphthoquinone	
CAS: 91-44-1	Colorant	
CAS: 13598-36-2	phosphorous acid	
CAS: 112945-52-5	Silicon dioxide, amorphous	
CAS: 21645-51-2	Alumina Trihydrate	
- Canad	- Canadian Non-Domestic Substances List (NDSL)	
CAS: 127-06-0 2-Propanone, oxime		
- Canadian Ingredient Disclosure list (limit 0.1%)		
None of the ingredients is listed.		
- Canad	- Canadian Ingredient Disclosure list (limit 1%)	
None of the ingredi	None of the ingredients is listed.	
<u> </u>		

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
- Classification System:
 - HMIS-ratings (scale 0 4)



- NFPA ratings (scale 0 - 4)



- Date of the latest revision of the safety data sheet 01/29/2024

- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Inc. believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries, Inc. assumes no legal responsibility for use or reliance thereon.