



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

1 Identification

- Product identifier

- Trade name: Vibra-TITE® VC-3®
 - Synonyms: VC-3 Threadmate
 - Part number: VT213
 - Application of the substance / the mixture Thread Locking
 - Thread locking and sealing

- Details of the supplier of the safety data sheet


- Manufacturer/Supplier: ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department

- Emergency telephone number: United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



Flammable Liquids 2

H225 Highly flammable liquid and vapor.



Eve Irritation 2A H319 Causes serious eye irritation. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



- Signal word Danger

- Hazard-determining components of labeling: methyl ethyl ketone
- Hazard statements
- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
- Precautionary statements
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep container tightly closed.
- Ground/bond container and receiving equipment. P240
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Page 1/7

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

- Other

Trade name: Vibra-TITE® VC-3®

Reviewed on 01/12/2024

			(Contd. of page 1)
	P280	Wear eye protection / face protection.	
	P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and	easy to do.
		Continue rinsing.	
	P312	Call a poison center/doctor if you feel unwell.	
	P337+P313	If eye irritation persists: Get medical advice/attention.	
	P370+P378	In case of fire: Use CO2, powder or water spray to extinguish.	
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
	P403+P235	Store in a well-ventilated place. Keep cool.	
	P405	Store locked up.	
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
r	[.] hazards		

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

CAS: 78-93-3 meth		
CAS. 70-93-3 metr	ethyl ethyl ketone	60 - 69%
Flan H33	ammable Liquids 2, H225; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, 336	
CAS: 28262-63-7 Acry	rylic Resin	30 – 39%
Com	ombustible Dust	

4 First-aid measures

- Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Generally the product does not irritate the skin.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.

- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

Suitable extinguishing agents:

- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Printing date 01/23/2024

Trade name: Vibra-TITE® VC-3®

(Contd. of page 2)

Reviewed on 01/12/2024

7 Handling and storage

- Handling:

- Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.

- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.

- Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits.

CAS	78-93-3 methyl ethyl ketone		
PEL	Long-term value: 590 mg/m ³ , 200 ppm		
REL	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm		
TLV	Short-term value: NIC-150 (300) ppm Long-term value: NIC-75 (200) ppm BEI, NIC-Skin		
	- Ingredients with biological limit values:		
CAS: 78-93-3 methyl ethyl ketone			
	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)		
	- Additional information: The lists that were valid during the creation were used as basis.		

- Exposure controls

Personal protective equipment:

- General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

(Contd. of page 3)

Printing date 01/23/2024

Trade name: Vibra-TITE® VC-3®

- Ignition temperature:

Reviewed on 01/12/2024

9 Physical and chemical properties				
- Information on basic physical and che - General Information - Appearance:	mical properties			
- Form:	Viscous			
- Color:	Red			
- Odor:	Solvent-like			
- Odor threshold:	Not determined.			
- pH-value:	Not determined.			
- Change in condition - Melting point/Melting range: - Boiling point/Boiling range:	Undetermined. ≥ 79 – ≤ 80.5 °C (≥ 174.2 – ≤ 176.9 °F)			
- Flash point:	≥ -4 °C (≥ 24.8 °F)			
- Flammability (solid, gaseous):	Highly flammable.			
- Auto igniting:	410 °C (770 °F)			
- Decomposition temperature:	Not determined.			

- Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- Explosion limits:	
- Lower:	1.8 Vol %
- Upper:	11.5 Vol %
- Vapor pressure at 20 °C (68 °F):	≤ 105 hPa (≤ 78.8 mm Hg)
- Density:	Not determined.
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
Partition apofficient (n astanol/wat	

Product is not selfigniting.

- Partition coefficient (n-octanol/water): Not determined.	
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic at 40 °C (104 °F):	250 mm²/s
- Solvent content:	
 Organic solvents: 	60.2 %
- VOC content:	60.20 %
	602.0 g/l / 5.02 lb/gal
- Solids content:	34.3 %
- Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.

- Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:
- Aldehyde

Hydrocarbons

Printing date 01/23/2024

Trade name: Vibra-TITE® VC-3®

(Contd. of page 4)

Reviewed on 01/12/2024

Information on toxicological effects - Acute toxicity:	
 LD/LC50 values that are relevant for classification: 	
CAS: 78-93-3 methyl ethyl ketone	
Oral LD50 3,300 mg/kg (rat)	
Dermal LD50 5,000 mg/kg (rabbit)	
- Primary irritant effect:	
- on the skin: No irritant effect.	
- on the eye: Irritating effect.	
- Sensitization: No sensitizing effects known.	
- Additional toxicological information:	
The product shows the following dangers according to internally approved calculation methods for preparati	ons:
	ons:
The product shows the following dangers according to internally approved calculation methods for preparation	ons:
The product shows the following dangers according to internally approved calculation methods for preparation Irritant	ons:
The product shows the following dangers according to internally approved calculation methods for preparation Irritant - Carcinogenic categories - IARC (International Agency for Research on Cancer)	
The product shows the following dangers according to internally approved calculation methods for preparation Irritant - Carcinogenic categories - IARC (International Agency for Research on Cancer) CAS: 108-88-3 toluene	
The product shows the following dangers according to internally approved calculation methods for preparation Irritant - Carcinogenic categories	ons:
The product shows the following dangers according to internally approved calculation methods for preparative Irritant - Carcinogenic categories - IARC (International Agency for Research on Cancer) CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol	
The product shows the following dangers according to internally approved calculation methods for preparative lirritant - Carcinogenic categories - IARC (International Agency for Research on Cancer) CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - NTP (National Toxicology Program)	
The product shows the following dangers according to internally approved calculation methods for preparative <i>- Carcinogenic categories - IARC (International Agency for Research on Cancer)</i> CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol <i>- NTP (National Toxicology Program)</i> None of the ingredients is listed.	

- Aquatic toxicity: No further relevant information available.

- Persistence and degradability No further relevant information available.

- Behavior in environmental systems:

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

- General notes:

- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - vPvB: Not applicable.

- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods

- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number - DOT, IMDG, IATA	UN1139	
UN proper shipping name		
- DOT	Coating solution	
- IMDG, IATA	COATING SOLUTION	

(Contd. on page 6)

Printing date 01/23/2024

Trade name: Vibra-TITE® VC-3®

Reviewed on 01/12/2024

Transport hazard class(es)	(Contd. of p
- DOT	
- Class - Label	3 Flammable liquids 3
- IMDG, IATA	
- Class - Label	3 Flammable liquids 3
Packing group - DOT, IMDG, IATA	II
Environmental hazards: - Marine pollutant:	Νο
Special precautions for user	Warning: Flammable liquids
- Hazard identification number (Kemler code):	33
- EMS Number: - Stowage Category	F-E, <u>S-E</u> B
Transport in bulk according to Annex II of MARPOL73/	
and the IBC Code	Not applicable.
Transport/Additional information:	
- DOT	
- Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
- IMDG	
- Limited quantities (LQ)	5L
 Excepted quantities (EQ) 	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml
UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, II
Regulatory information	
Safety, health and environmental regulations/legislatic No further relevant information available. - Sara	on specific for the substance or mixture
- Section 355 (extremely hazardous substance	es):
None of the ingredients is listed.	
 Section 313 (Specific toxic chemical listings) 	
CAS: 108-88-3 toluene	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act):	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act): All components have the value ACTIVE.	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act): All components have the value ACTIVE. - Hazardous Air Pollutants	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act): All components have the value ACTIVE. - Hazardous Air Pollutants CAS: 108-88-3 toluene	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act): All components have the value ACTIVE. - Hazardous Air Pollutants CAS: 108-88-3 toluene - Proposition 65	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act): All components have the value ACTIVE. - Hazardous Air Pollutants CAS: 108-88-3 toluene - Proposition 65 - Chemicals known to cause cancer:	
CAS: 108-88-3 toluene CAS: 111-76-2 2-butoxyethanol - TSCA (Toxic Substances Control Act): All components have the value ACTIVE. - Hazardous Air Pollutants CAS: 108-88-3 toluene - Proposition 65	

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

Trade name: Vibra-TITE® VC-3®

		(Contu. or page o
- Ch	emicals known to cause reproductive toxicity for males:	
None of the ing	edients is listed.	
- Ch	emicals known to cause developmental toxicity:	
CAS: 108-88-3	toluene	
- Carcir	ogenic categories	
- EP	A (Environmental Protection Agency)	
CAS: 78-93-3	methyl ethyl ketone	1
CAS: 108-88-3	toluene	
CAS: 111-76-2	2-butoxyethanol	NL
- TL	/ (Threshold Limit Value)	
CAS: 108-88-3	toluene	A4
CAS: 111-76-2	2-butoxyethanol	A3
- NIC	OSH-Ca (National Institute for Occupational Safety and Heal	th)
None of the ind	redients is listed	-

None of the ingredients is listed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affaires

- Contact: Safety, Health and Environmental Affaires

- Classification System:

- HMIS-ratings (scale 0 - 4)



- NFPA ratings (scale 0 - 4)



- Date of preparation / last revision 01/23/2024

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

- REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.

Reviewed on 01/12/2024