



Page 1/8

Reviewed on 01/04/2024

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

1 Identification

- Product identifier

- Trade name: Vibra-TITE® Thread Sealant
 - Synonyms: 420 Controlled Strength Slow Cure Thread Sealant
 - Part number: VT420
 - Application of the substance / the mixture Thread Sealant
 - Sealing Sealant
- Details of the supplier of the safety data sheet
 - Manufacturer/Supplier: ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com
 - Information department: Product Safety Department
 - *Emergency telephone number:* United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture

GHS08 Health hazard

Carcinogenicity 2H351 Suspected of causing cancer.Specific Target Organ Toxicity - Repeated Exposure 2H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irritation 2 Eye Irritation 2A Specific Target Organ Toxicity - Single Exposure 3 H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



- Signal word Warning
- Hazard-determining components of labeling: 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate
- dimethylbenzyl hydroperoxide
- Hazard statements
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 1)

Reviewed on 01/04/2024

H351 Suspected o	f causing cancer.
H335 May cause r	espiratory irritation.
H373 May cause d	lamage to organs through prolonged or repeated exposure.
Precautionary s	statements
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P280	Wear eye protection / face protection.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED. Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
hazards	

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- Other

- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate	40 - 49%
	Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	
CAS: 9004-36-8	Cellulose Acetate Butyrate	5 – 9%
	Combustible Dust	
CAS: 80-15-9	dimethylbenzyl hydroperoxide	1 – 4%
	Self-reactive substances and mixtures - Type F, H242; Organic Peroxides - Type E, H242; Acute Toxicity - Inhalation 3, H331; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304; Skin Corrosion 1B, H314; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Specific Target Organ Toxicity - Single Exposure 3, H335; Flammable Liquids 4, H227	
CAS: 613-48-9	N,N-Diethyl-P-Toluidine	≤ 1%
	Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Eye Irritation 2A, H319; Flammable Liquids 4, H227	
CAS: 609-72-3	N,N-dimethyl-o-toluidine	≤ 1%
	Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; Skin Irritation 2, H315; Eye Irritation 2A, H319; Flammable Liquids 4, H227	
CAS: 98-82-8	Cumene	≤ 1%
	Flammable Liquids 3, H226; Carcinogenicity 2, H351; Aspiration Hazard 1, H304; Acute Toxicity - Oral 4, H302; Specific Target Organ Toxicity - Single Exposure 3, H335	

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

- Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available. - Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. of page 2)

Printing date 01/23/2024

Trade name: Vibra-TITE® Thread Sealant

Reviewed on 01/04/2024

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents: Use fire fighting measures that suit the environment.

- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters

- Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
 Wear protective clothing.

 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.

- Control parameters

Components with limit values that require monitoring at the workplace:

At this time, the other constituents have no known exposure limits.

CAS: 80-15-9 dimethylbenzyl hydroperoxide		
WEEL	Long-term value: 6 mg/m³, 1 ppm Skin	
CAS: 98-82-8 Cumene		
PEL	Long-term value: 245 mg/m³, 50 ppm Skin	
REL	Long-term value: 245 mg/m³, 50 ppm Skin	
TLV	Long-term value: 5 ppm A3	
- Additional information: The lists that were valid during the creation were used as basis.		

- Exposure controls

- Personal protective equipment:
 - General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

Printing date 01/23/2024

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 3)

Reviewed on 01/04/2024

- Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. - **Eye protection:** Required use of safety glasses

- Body protection: Protective work clothing

9 Physical and chemical properties

a rivisical and chemical properties		
- Information on basic physical and cher - General Information - Appearance:		
- Form:	Viscous	
- Color:	White	
- Odor:	Characteristic	
- Odor threshold:	Not determined.	
- pH-value:	Not determined.	
- Change in condition - Melting point/Melting range: - Boiling point/Boiling range:	Undetermined. ≥ 200 °C (≥ 392 °F)	
- Flash point:	131 °C (267.8 °F)	
- Flammability (solid, gaseous):	Not applicable.	
 Decomposition temperature: 	Not determined.	
- Ignition temperature:	Product is not selfigniting.	
- Danger of explosion:	Product does not present an explosion hazard.	
- Explosion limits: - Lower: - Upper:	Not determined. Not determined.	
- Vapor pressure at 20 °C (68 °F):	≤ 53 hPa (≤ 39.8 mm Hg)	
- Density:	Not determined.	
- Relative density	Not determined.	
- Vapor density	Not determined.	
- Evaporation rate	Not determined.	
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
- Partition coefficient (n-octanol/water): Not determined.		
- Viscosity: - Dynamic: - Kinematic:	Not determined. Not determined.	
	Hot dotominou.	
- Solvent content: - Organic solvents: - Water: - VOC content:	0.9 % 0.3 % 0.87 % 8.7 g/l / 0.07 lb/gal	

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

Trade name: Vibra-TITE® Thread Sealant

Reviewed on 01/04/2024

 - Solids content:
 65.0 %

 - Other information
 No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.

- Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.

- Conditions to avoid No further relevant information available.

- Incompatible materials: No further relevant information available.

- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	6,663 mg/kg
Dermal	LD50	14,401 mg/kg
Inhalative	LC50/4 h	279 mg/l
CAS: 9004	4-36-8 Cel	lulose Acetate Butyrate
Oral	LD50	> 6,400 mg/kg (rabbit)
Dermal	LD50	> 1,000 mg/kg (rabbit)
CAS: 80-1	5-9 dimet	hylbenzyl hydroperoxide
Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)
CAS: 613-	48-9 N,N-I	Diethyl-P-Toluidine
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)
CAS: 609-72-3 N,N-dimethyl-o-toluidine		
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)
CAS: 98-82-8 Cumene		
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)
- Di	rimarv irr	itant effect:

Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.

- on the eye: Irritating effect.

- Sensitization: No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- Carcinogenic categories

- IAR	C (International Agency for Research on Cancer)	
CAS: 9002-84-0	Polytetrafluoroethylene	3
CAS: 13463-67-7	7 titanium dioxide	2B
CAS: 98-82-8	Cumene	2B
CAS: 111-76-2	2-butoxyethanol	3
- NTP	P (National Toxicology Program)	
CAS: 98-82-8 C	umene	R
		(Contri on norro C)

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

Trade name: Vibra-TITE® Thread Sealant

Reviewed on 01/04/2024

(Contd. of page 5)

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- Aquatic toxicity: No further relevant information available.

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods

- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

- UN-Number - DOT, ADN, IMDG, IATA	not regulated	
- UN proper shipping name - DOT, ADN, IMDG, IATA	not regulated	
- Transport hazard class(es)		
- DOT, ADN, IMDG, IATA - Class	not regulated	
- Packing group - DOT, IMDG, IATA	not regulated	
- Environmental hazards: - Marine pollutant:	No	
- Special precautions for user	Not applicable.	
 Transport in bulk according to Annex II of and the IBC Code 	f MARPOL73/78 Not applicable.	
- UN "Model Regulation":	not regulated	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

- Sara
- Section 355 (extremely hazardous substances):
None of the ingredients is listed.
- Section 313 (Specific toxic chemical listings):
CAS: 80-15-9 dimethylbenzyl hydroperoxide
CAS: 98-82-8 Cumene
CAS: 98-86-2 acetophenone
CAS: 98-86-2 acetophenone
CAS: 111-76-2 2-butoxyethanol
- TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.

(Contd. of page 6)

Trade name: Vibra-TITE® Thread Sealant

Reviewed on 01/04/2024

		· · · · · ·
- Ha	zardous Air Pollutants	
CAS: 98-82-8	Jumene	
CAS: 98-86-2	icetophenone	
- Propo	sition 65	
- Ch	emicals known to cause cancer:	
CAS: 98-82-8	Jumene	
- Ch	emicals known to cause reproductive toxicity for females:	
None of the ing	redients is listed.	
- Ch	emicals known to cause reproductive toxicity for males:	
None of the ing	redients is listed.	
- Ch	emicals known to cause developmental toxicity:	
None of the ing	redients is listed.	
- Carcir	ogenic categories	
- EP	A (Environmental Protection Agency)	
CAS: 98-82-8	Cumene	D, CBI
CAS: 98-86-2	acetophenone	D
CAS: 111-76-2	2-butoxyethanol	NL
- TL	V (Threshold Limit Value)	
CAS: 13463-67	-7 titanium dioxide	A
CAS: 111-76-2	2-butoxyethanol	A
- NI	OSH-Ca (National Institute for Occupational Safety and Health)	
CAS: 13463-67	-7 titanium dioxide	
- Chemical sa	ety assessment: A Chemical Safety Assessment has not been carried οι	Jt.
6 Other inform		

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affaires

- Contact: Safety, Health and Environmental Affaires

- Classification System:

- HMIS-ratings (scale 0 - 4)



- NFPA ratings (scale 0 - 4)



- Date of preparation / last revision 01/23/2024

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids Category 3
- Flammable Liquids 4: Flammable liquids Category 4
- Self-reactive substances and mixtures Type E/F Organic Peroxides Type E: Organic peroxides Type E/F Acute Toxicity Oral 4: Acute toxicity Category 4 Acute Toxicity Inhalation 3: Acute toxicity Category 3 Skin Corrosion 1B: Skin corrosion/irritation Category 18

- Skin Irritation 2: Skin corrosion/irritation Category 2 Eye Damage 1: Serious eye damage/eye irritation Category 1

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/04/2024

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 7)

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 Aspiration Hazard 1: Aspiration hazard – Category 1

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.