

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

**1 Identification****- Product identifier**

- **Trade name:** Vibra-TITE® Thread Sealant
- **Synonyms:** 486 Multi-Purpose Thread Sealant
- **Part number:** VT486
- **Application of the substance / the mixture**
  - Sealing
  - Sealant

**- Details of the supplier of the safety data sheet****- Manufacturer/Supplier:**

ND Industries, Inc  
1000 North Crooks Road  
Clawson, MI 48017  
USA  
Telephone: +1-248-288-0000  
Email: info@ndindustries.com  
Website: www.ndindustries.com

**- Information department:** Product Safety Department**- Emergency telephone number:**

United States: 1-800-424-9300  
International: +1-703-527-3887

**2 Hazard(s) identification****- Classification of the substance or mixture**

GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to organs through prolonged or repeated exposure.

**- Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**- Hazard pictograms**

GHS02 GHS08

**- Signal word** Danger**- Hazard-determining components of labeling:**

Soapstone  
ethanol

**- Hazard statements**

H225 Highly flammable liquid and vapor.  
H350 May cause cancer.  
H372 Causes damage to organs through prolonged or repeated exposure.

**- Precautionary statements**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

**Trade name:** Vibra-TITE® Thread Sealant

(Contd. of page 1)

|                |   |
|----------------|---|
| P264           | Wash thoroughly after handling.   |
| P270           | Do not eat, drink or smoke when using this product.   |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.                          |
| P303+P361+P353 | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P308+P313      | If exposed or concerned: Get medical advice/attention.  |
| P314           | Get medical advice/attention if you feel unwell.  |
| P370+P378      | In case of fire: Use CO <sub>2</sub> , powder or water spray to extinguish.                         |
| P403+P235      | Store in a well-ventilated place. Keep cool.  |
| P405           | Store locked up.  |
| P501           | Dispose of contents/container in accordance with local/regional/national/international regulations. |

**- Other hazards****- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

**- Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

**- Dangerous components:**

|                 |               |  |          |
|-----------------|---------------|--|----------|
| CAS: 14807-96-6 | Soapstone     | Carcinogenicity 1A, H350; Specific Target Organ Toxicity - Repeated Exposure 1, H372 | 30 – 39% |
| CAS: 64-17-5    | ethanol       | Flammable Liquids 2, H225; Carcinogenicity 1A, H350                                  | 20 – 29% |
| CAS: 63148-65-2 | Binding agent | Combustible Dust   | 5 – 9%   |

### 4 First-aid measures

**- Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
  - **Most important symptoms and effects, both acute and delayed** No further relevant information available.
  - **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

**- Extinguishing media****- Suitable extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**- For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture** No further relevant information available.

**- Advice for firefighters****- Protective equipment:**

Wear self-contained respiratory protective device.  
Wear fully protective suit.

### 6 Accidental release measures

**- Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**- Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

**- Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 2)

## 7 Handling and storage

### - Handling:

#### - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

#### - Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

### - Conditions for safe storage, including any incompatibilities

#### - Storage:

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

#### - Further information about storage conditions:

Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

### - Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

### - Control parameters

#### - Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### CAS: 64-17-5 ethanol

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

TLV Short-term value: 1000 ppm  
A3

- **Additional information:** The lists that were valid during the creation were used as basis.

### - Exposure controls

#### - Personal protective equipment:

- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

#### - Breathing equipment:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### - Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

#### - Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### - Eye protection:



Tightly sealed goggles

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

### - Information on basic physical and chemical properties

#### - General Information

#### - Appearance:

##### - Form:

Viscous

##### - Color:

Whitish

#### - Odor:

Characteristic

#### - Odor threshold:

Not determined.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 3)

|   |  |
|---|--|
| - <b>pH-value:</b>                                | Not determined.  |
| - <b>Change in condition</b>                      |  |
| - <b>Melting point/Melting range:</b>             | Undetermined.  |
| - <b>Boiling point/Boiling range:</b>             | ≥ 78 °C (≥ 172.4 °F)   |
| - <b>Flash point:</b>                             | 13 °C (55.4 °F)  |
| - <b>Flammability (solid, gaseous):</b>           | Highly flammable.  |
| - <b>Auto igniting:</b>                           | 425 °C (797 °F)  |
| - <b>Decomposition temperature:</b>               | Not determined.  |
| - <b>Ignition temperature:</b>                    | Product is not selfigniting.   |
| - <b>Danger of explosion:</b>                     | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| - <b>Explosion limits:</b>                        |  |
| - <b>Lower:</b>                                   | 3.5 Vol %  |
| - <b>Upper:</b>                                   | 15 Vol %   |
| - <b>Vapor pressure at 20 °C (68 °F):</b>         | ≤ 59 hPa (≤ 44.3 mm Hg)  |
| - <b>Density at 20 °C (68 °F):</b>                | ~ 0.97475 g/cm <sup>3</sup> (~ 8.13429 lbs/gal)  |
| - <b>Relative density</b>                         | Not determined.  |
| - <b>Vapor density</b>                            | Not determined.  |
| - <b>Evaporation rate</b>                         | Not determined.  |
| - <b>Solubility in / Miscibility with</b>         |  |
| - <b>Water:</b>                                   | Not miscible or difficult to mix.  |
| - <b>Partition coefficient (n-octanol/water):</b> | Not determined.  |
| - <b>Viscosity:</b>                               |  |
| - <b>Dynamic:</b>                                 | Not determined.  |
| - <b>Kinematic:</b>                               | Not determined.  |
| - <b>Solvent content:</b>                         |  |
| - <b>Organic solvents:</b>                        | 20.0 %   |
| - <b>Water:</b>                                   | 0.2 %  |
| - <b>VOC content:</b>                             | 20.00 %<br>~ 195.0 g/l / ~ 1.63 lb/gal   |
| - <b>Solids content:</b>                          | 49.8 %   |
| - <b>Other information</b>                        | No further relevant information available.   |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

CAS: 64-17-5 ethanol

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 7,060 mg/kg (rat) |
| Inhalative | LC50/4 h | 20,000 mg/l (rat) |

- **Primary irritant effect:**
  - **on the skin:** No irritant effect.
  - **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 4)

**- Additional toxicological information:****- Carcinogenic categories****- IARC (International Agency for Research on Cancer)**

|                 |                         |    |
|-----------------|-------------------------|----|
| CAS: 14807-96-6 | Soapstone               | 3  |
| CAS: 64-17-5    | ethanol                 | 1  |
| CAS: 13463-67-7 | titanium dioxide        | 2B |
| CAS: 9002-84-0  | Polytetrafluoroethylene | 3  |

**- NTP (National Toxicology Program)**

None of the ingredients is listed.

**- OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information****- Toxicity****- Aquatic toxicity:** No further relevant information available.**- Persistence and degradability** No further relevant information available.**- Behavior in environmental systems:****- Bioaccumulative potential** No further relevant information available.**- Mobility in soil** No further relevant information available.**- Additional ecological information:****- General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**- Results of PBT and vPvB assessment****- PBT:** Not applicable.**- vPvB:** Not applicable.**- Other adverse effects** No further relevant information available.**13 Disposal considerations****- Waste treatment methods****- Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**- Uncleaned packagings:****- Recommendation:** Disposal must be made according to official regulations.**\*14 Transport information****- UN-Number****- DOT, IMDG, IATA**

UN1170

**- UN proper shipping name****- DOT**

Ethanol solutions

**- IMDG**

ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

**- IATA**

ETHANOL SOLUTION

**- Transport hazard class(es)****- DOT****- Class**

3 Flammable liquids

**- Label**

3

**- IMDG, IATA****- Class**

3 Flammable liquids

**- Label**

3

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 5)

|  |   |
|--|---|
| - <b>Packing group</b><br>- <b>DOT, IMDG, IATA</b>   | II  |
| - <b>Environmental hazards:</b><br>- <b>Marine pollutant:</b>  | No  |
| - <b>Special precautions for user</b><br>- <b>Hazard identification number (Kemler code):</b><br>- <b>EMS Number:</b><br>- <b>Stowage Category</b> | Warning: Flammable liquids<br>33<br>F-E,S-D<br>A  |
| - <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>   | Not applicable.   |
| - <b>Transport/Additional information:</b><br>- <b>DOT</b><br>- <b>Quantity limitations</b>  | On passenger aircraft/rail: 5 L<br>On cargo aircraft only: 60 L   |
| - <b>IMDG</b><br>- <b>Limited quantities (LQ)</b><br>- <b>Excepted quantities (EQ)</b>   | 1L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| - <b>UN "Model Regulation":</b>  | UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION),<br>3, II   |

## 15 Regulatory information

### - Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

#### - Sara

##### - Section 355 (extremely hazardous substances):

None of the ingredients is listed.

##### - Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

##### - TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

##### - Hazardous Air Pollutants

None of the ingredients is listed.

##### - Proposition 65

##### - Chemicals known to cause cancer:

None of the ingredients is listed.

##### - Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

##### - Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

##### - Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

##### - Carcinogenic categories

##### - EPA (Environmental Protection Agency)

None of the ingredients is listed.

##### - TLV (Threshold Limit Value)

|                 |                  |    |
|-----------------|------------------|----|
| CAS: 14807-96-6 | Soapstone        | A4 |
| CAS: 64-17-5    | ethanol          | A3 |
| CAS: 13463-67-7 | titanium dioxide | A4 |

##### - NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 13463-67-7 titanium dioxide

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 10/23/2023

Trade name: Vibra-TITE® Thread Sealant

(Contd. of page 6)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs
- **Contact:** Safety, Health and Environmental Affairs
- **Classification System:**

- **HMIS-ratings (scale 0 - 4)**

|            |    |                |
|------------|----|----------------|
| HEALTH     | 10 | Health = *0    |
| FIRE       | 3  | Fire = 3       |
| REACTIVITY | 0  | Reactivity = 0 |

- **NFPA ratings (scale 0 - 4)**

|   |   |   |                |
|---|---|---|----------------|
| 0 | 3 | 0 | Health = 0     |
|   |   |   | Fire = 3       |
|   |   |   | Reactivity = 0 |

- **Date of preparation / last revision** 01/23/2024

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Flammable Liquids 2: Flammable liquids – Category 2  
 Carcinogenicity 1A: Carcinogenicity – Category 1A  
 Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

- \* **Data compared to the previous version altered.**

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,  
 ®Vibra-TITE is a registered trademark of ND Industries, Inc.