



Page 1/8

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/29/2024 Reviewed on 01/29/2024

1 Identification

- Product identifier
 - Trade name: Vibra-TITE® Excel Structural Activator
 - Synonyms: 638 Excel Structural Activator
 - Part number: VT638
 - Application of the substance / the mixture Activator
- Details of the supplier of the safety data sheet
 - Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department
- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard identification

- Classification of the substance or mixture



Flammable Liquids - Category 2 H225 Highly flammable liquid and vapour.



GHS08 Health hazard

Aspiration Hazard - Category 1 H304 May be fatal if swallowed and enters airways.



Skin Irritation - Category 2 Eye Irritation - Category 2A H315 Causes skin irritation.

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3 H336 May cause drowsiness or dizziness.

- Label elements
 - GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms







GHS02 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling:

heptane isopropanol

Distillates (petroleum), hydrotreated light

Stoddard solvent

- Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

- Precautionary statements

(Contd. of page 1)

No smoking

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P242	Use non-sparking tools.
1 242	Ose non-sparking tools.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P280 Wear protective gloves.

P301+P310 If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label). P321

P331 Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Call a poison center/doctor if you feel unwell. P312 P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations P501

3 Composition/Information on ingredients

- Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 142-82-5	heptane	30 – 60% w/w
	Flammable Liquids - Category 2, H225; Aspiration Hazard - Category 1, H304; Skin Irritation - Category 2, H315; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	
CAS: 67-63-0	isopropanol	10 – 30% w/w
	Flammable Liquids - Category 2, H225; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H336	
CAS: 34562-31-7	7 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	10 – 30% w/w
	Acute Toxicity (Oral) - Category 4, H302; Acute Toxicity (Dermal) - Category 4, H312; Skin Irritation - Category 2, H315; Eye Irritation - Category 2B, H320	

4 First-aid measures

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed

No further relevant information available

5 Fire-fighting measures

- Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 2)

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters

Medium: urine

Time: end of shift at end of workweek

- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

1110 101101	wing constituents are the only constituents of the product which have a real, rev or other recommended exposure limit.		
CAS: 142-82-	CAS: 142-82-5 heptane		
EL (Canada)	STEL: 500 ppm TWA: 400 ppm		
EV (Canada)	STEL: 2.045 mg/m³, 500 ppm TWA: 1.635 mg/m³, 400 ppm		
PEL (USA)	TWA: 2000 mg/m³, 500 ppm		
REL (USA)	TWA: 350 mg/m³, 85 ppm Ceiling: 1800* mg/m³, 440* ppm *15-min		
TLV (USA)	STEL: 500 ppm TWA: 400 ppm		
CAS: 67-63-0	CAS: 67-63-0 isopropanol		
EL (Canada)	STEL: 400 ppm TWA: 200 ppm		
EV (Canada)	STEL: 400 ppm TWA: 200 ppm		
PEL (USA)	TWA: 980 mg/m³, 400 ppm		
REL (USA)	STEL: 1225 mg/m³, 500 ppm TWA: 980 mg/m³, 400 ppm		
TLV (USA)	STEL: 400 ppm TWA: 200 ppm BEI, A4		
- Ir	ngredients with biological limit values:		
CAS: 67-63-0	CAS: 67-63-0 isopropanol		
BEI (USA) 40) mg/L		

Parameter: Acetone (background, nonspecific)

- Additional information: The lists that were valid during the creation were used as basis.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 3)

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties General Information - Appearance: - Form: - Cotlor: - Odor: - Odor: - Odor threshold: Not determined. - PH-value: - Change in condition - Melting point/Melting range: - Boiling point/Boiling range: - Boiling point/Boiling range: - Highly flammable. - Flammability (solid, gaseous): - Highly flammable. - Auto igniting: - Decomposition temperature: - Ignition temperature: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor pressure at 50 °C: - Relative density - Vapor pressure - Explosion rate - Solubility in / Miscibility with - Water: - Not miscible or difficult to mix Partition coefficient (n-octanol/water): Not determined Not miscible or difficult to mix.	Information on boois abyoical and abo	mical proportion
- Appearance: - Form: - Color: - Color: - Odor: - Odor threshold: - PH-value: - Change in condition - Melting point/Melting range: - Boiling point/Melting range: - Boiling point/Melting range: - Boiling point/Melting range: - Highly flammable Flammability (solid, gaseous): - Flash point: - Auto igniting: - Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Product is not selfigniting Danger of explosion: - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		micai properties
Fluid According to product specification Characteristic Not determined. PH-value: Not determined. Change in condition - Melting point/Melting range: Boiling point/Boiling range: - Boiling point/Boiling range: - Highly flammable. Ludetermined. PFlash point: -4 °C Flammability (solid, gaseous): Highly flammable. Auto igniting: - Loeomposition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapor mixtures are possible. Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Pelastive density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		
- Color: - Odor: - Odor threshold: - pH-value: - Change in condition - Melting point/Melting range: - Boiling point/Boiling range: - Vapcor position temperature: - Ignition temperature: - Ignition temperature: - Product is not selfigniting Danger of explosion: - Explosion limits: - Lower: - Lower: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Explosion rate - Solubility in / Miscibility with - Water: - Not determined Not miscible or difficult to mix.	• •	-
- Odor: - Odor threshold: - pH-value: - Change in condition - Melting point/Melting range: - Boiling point/Boiling range: - Boiling point/Boiling range: - Flash point: - 4° C - Flammability (solid, gaseous): - Highly flammable Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor density - Exaporation rate - Solubility in / Miscibility with - Water: Not determined Not determined Solubility in / Miscibility with - Water: Not determined. Not miscible or difficult to mix.		
- Odor threshold: - pH-value: - Change in condition - Melting point/Melting range: - Boiling point/Boiling range: - Boiling point/Boiling range: - Flash point: - Flammability (solid, gaseous): - Highly flammable. - Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - Upper: - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor density - Vapor and the side of the first of the product is not explosive Solubility in / Miscibility with - Water: Not determined Not determined Solubility in / Miscibility with - Water: - Not miscible or difficult to mix.	00.0	0 1
- pH-value: - Change in condition - Melting point/Melting range: - Boiling point/Boiling range: - Boiling point/Boiling range: - Flash point: - Flammability (solid, gaseous): - Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Product is not selfigniting. - Danger of explosion: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - 11 Vol % - 12 Vol % - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not determined. Not miscible or difficult to mix.	0.00	
- Change in condition - Melting point/Melting range: - Boiling point/Boiling range: - Flash point: - 4 °C - Flammability (solid, gaseous): - Highly flammable Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Product is not selfigniting Danger of explosion: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible Explosion limits: - Lower: - Upper: - 1.1 Vol % - 12 Vol % - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: - Not miscible or difficult to mix.	- Odor threshold:	Not determined.
- Melting point/Melting range: - Boiling point/Boiling range: - Flash point: - 4° C - Flammability (solid, gaseous): - Highly flammable. - Auto igniting: - Decomposition temperature: - Ignition temperature: - Product is not selfigniting. - Danger of explosion: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor density - Explosibility in / Miscibility with - Water: - Not miscible or difficult to mix.	- pH-value:	Not determined.
- Boiling point/Boiling range: - Flash point: - Flammability (solid, gaseous): - Highly flammable. - Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Danger of explosion: - Danger of explosion: - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: - Water: - Wighly flammable. - Highly flammable. - Not determined. - Not miscible or difficult to mix.	- Change in condition	
- Boiling point/Boiling range: - Flash point: - Flammability (solid, gaseous): - Highly flammable. - Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Danger of explosion: - Product is not selfigniting. - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Vaporation rate - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.	- Melting point/Melting range:	Undetermined.
- Flash point: - Flammability (solid, gaseous): - Highly flammable Auto igniting: - Decomposition temperature: - Ignition temperature: - Ignition temperature: - Product is not selfigniting Danger of explosion: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - 12 Vol % - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		≥ 82 °C
- Flammability (solid, gaseous): - Auto igniting: - Decomposition temperature: - Ignition temperature: - Product is not selfigniting. - Danger of explosion: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - 1.1 Vol % 12 Vol % - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Vapor density - Vapor density - Evaporation rate Not determined. - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.	<u> </u>	1 °C
- Auto igniting: - Decomposition temperature: - Ignition temperature: - Danger of explosion: - Danger of explosion: - Explosion limits: - Lower: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Explosiolity in / Miscibility with - Water: - Not determined. Not miscible or difficult to mix.	•	<u> </u>
- Decomposition temperature: - Ignition temperature: - Product is not selfigniting Danger of explosion: - Product is not explosive. However, formation of explosive air/vapor mixtures are possible. - Explosion limits: - Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not determined. Not miscible or difficult to mix.	- Flammability (solid, gaseous):	Highly flammable.
- Ignition temperature: - Danger of explosion: - Explosion limits: - Lower: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Relative density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor density - Not miscible or difficult to mix.	- Auto igniting:	215 °C
- Danger of explosion: - Explosion limits: - Lower: - Upper: - Vapor pressure at 20 °C: - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. 1.1 Vol % 1.1 Vol % 1.2 Vol % 48 hPa 2 48 hPa 2 190 hPa - 0.75168 g/cm³ Not determined. Not determined. Not determined. Not determined.	- Decomposition temperature:	Not determined.
possible. - Explosion limits: - Lower: - Upper: - Upper: - 12 Vol % - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Vapor pressure at 50 °C: - Selative density - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.	- Ignition temperature:	Product is not selfigniting.
- Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Vapor pressure at 50 °C: - Density at 20 °C: - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: - Not miscible or difficult to mix.	- Danger of explosion:	
- Lower: - Upper: - Upper: - Vapor pressure at 20 °C: - Vapor pressure at 50 °C: - Vapor pressure at 50 °C: - Density at 20 °C: - Relative density - Vapor density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: - Not miscible or difficult to mix.	- Explosion limits:	
- Upper: 12 Vol % - Vapor pressure at 20 °C: ≤ 48 hPa - Vapor pressure at 50 °C: ≤ 190 hPa - Density at 20 °C: ~ 0.75168 g/cm³ - Relative density Not determined Vapor density Not determined Evaporation rate Not determined Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		1.1 Vol %
- Vapor pressure at 20 °C: ≤ 48 hPa - Vapor pressure at 50 °C: ≤ 190 hPa - Density at 20 °C: ~ 0.75168 g/cm³ - Relative density Not determined Vapor density Not determined Evaporation rate Not determined Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		12 Vol %
- Vapor pressure at 50 °C: ≤ 190 hPa - Density at 20 °C: ~ 0.75168 g/cm³ - Relative density Not determined Vapor density Not determined Evaporation rate Not determined Solubility in / Miscibility with - Water: Not miscible or difficult to mix.	- Vanor pressure at 20 °C	< 49 hPa
- Density at 20 °C: ~ 0.75168 g/cm³ - Relative density Not determined Vapor density Not determined Evaporation rate Not determined Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		· · · · · ·
- Relative density - Vapor density - Evaporation rate - Solubility in / Miscibility with - Water: Not determined. Not determined. Not determined. Not miscible or difficult to mix.		
- Vapor density Not determined Evaporation rate Not determined Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		•
- Evaporation rate Not determined. - Solubility in / Miscibility with - Water: Not miscible or difficult to mix.	•	Not determined.
- Solubility in / Miscibility with - Water: Not miscible or difficult to mix.		Not determined.
- Water: Not miscible or difficult to mix.	 Evaporation rate 	Not determined.
- Water: Not miscible or difficult to mix.	- Solubility in / Miscibility with	
- Partition coefficient (n-octanol/water): Not determined.		Not miscible or difficult to mix.
	- Partition coefficient (n-octanol/wate	er): Not determined.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 4)

- Viscosity: - Dynamic: - Kinematic:	Not determined. Not determined.
- Solvent content: - Organic solvents: - VOC content:	85.0 % 84.98 % ~ 638.8 g/l / ~ 5.33 lb/gal
- Solids content:	0.0 %
- Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:

- LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	3,333 mg/kg
Dermal	LD50	7,333 mg/kg
CAS: 67-6	3-0 isopro	ppanol
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
CAS: 34562-31-7 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine		
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)	
CAS: 67-63-0 isopropanol	3
- NTP (National Toxicology Program)	
None of the ingredients is listed.	

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Ecotoxical effects:
 - Remark: Very toxic for fish

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 5)

- Additional ecological information:

- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - **Recommendation:** Disposal must be made according to official regulations.

t	14	Transp	ort info	rmation
---	----	--------	----------	---------

14 Transport information	
- UN-Number - DOT/TDG, ADR, IMDG, IATA	UN1993
- UN proper shipping name - DOT/TDG - ADR	Flammable liquids, n.o.s. (Heptanes, Isopropanol) UN1993 Flammable liquids, n.o.s. (Heptanes, Isopropanol), ENVIRONMENTALLY HAZARDOUS
- IMDG - IATA	FLAMMABLE LIQUID, N.O.S. (HEPTANES, ISOPROPANOL (ISOPROPYL ALCOHOL)), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (HEPTANES, ISOPROPANOL (ISOPROPYL ALCOHOL))
- Transport hazard class(es)	(ISOFNOFTE ALCOHOL))
- DOT/TDG (Transport dangerous goods):	
1 1 1 1 1 1 1 1 1 1	
- Class - Label	3 Flammable liquids 3
- ADR, IMDG	
1 1 1 1 1 1 1 1 1 1	
- Class - Label	3 Flammable liquids 3
- IATA	
- Class - Label	3 Flammable liquids 3
- Packing group - DOT/TDG, ADR, IMDG, IATA	II
- Environmental hazards: - Marine pollutant:	Product contains environmentally hazardous substances: heptane Yes Symbol (fish and tree)
- Special marking (ADR):	Symbol (fish and tree)
 Special precautions for user Hazard identification number (Kemler code): EMS Number: 	Warning: Flammable liquids 33 F-E, <u>S-E</u>

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 6)

- Stowage Category	В
- Transport in bulk according to Annex II of Ma and the IBC Code	ARPOL73/78 Not applicable.
- Transport/Additional information:	
- DOT/TDG - Quantity limitations - Remarks:	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L Special marking with the symbol (fish and tree).
- ADR - Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEPTANES, ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

- Sara

Curu			
- Section 355 (extremely hazardous substances):			
None of the ingredients is listed.			
- Section 313 (Specific toxic chemical listings):			
CAS: 67-63-0 isopropanol			
CAS: 1338-02-9 Metal Salt Complex			
- TSCA (Toxic Substances Control Act):			
heptane	ACTIVE		
isopropanol	ACTIVE		
3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	ACTIVE		
Metal Salt Complex	ACTIVE		
Distillates (petroleum), hydrotreated light	ACTIVE		
nonane	ACTIVE		
Naphthenic Acids	ACTIVE		

- Canadian substance listings:

- Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
- Canadian Non-Domestic Substances List (NDSL)	
None of the ingredients is listed.	
- Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
- Canadian Ingredient Disclosure list (limit 1%)	
CAS: 142-82-5 heptane	
CAS: 67-63-0 isopropanol	
Chamical astaty acceptants A Chamical Safaty Assessment has not been carried out	

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires

(Contd. of page 7)

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Excel Structural Activator

- Classification System:

- HMIS-ratings (scale 0 - 4)



- NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- Date of the latest revision of the safety data sheet 01/29/2024

- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

IMDIG: International Manume Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.