



Page 1/8

# Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024 Reviewed on 01/23/2024

# 1 Identification

- Product identifier
  - Trade name: Vibra-TITE® Excel Structural Activator
    - Synonyms: 638 Excel Structural Activator
    - Part number: VT638
    - Application of the substance / the mixture Activator
- Details of the supplier of the safety data sheet
  - Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department
- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

# 2 Hazard(s) identification

- Classification of the substance or mixture



Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



Skin Irritation 2

Eye Irritation 2A

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

- Label elements
  - GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
    - Hazard pictograms







GHS02 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labeling:

heptane isopropanol

Distillates (petroleum), hydrotreated light

Stoddard solvent

- Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 1)

## - Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.		
P233	Keep container tightly closed.		
P240	Ground/bond container and receiving equipment.		
P241	Use explosion-proof electrical/ventilating/lighting/equipment.		
P242	Use only non-sparking tools.		
P271	Use only outdoors or in a well-ventilated area.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P280	Wear eye protection / face protection.		
P301+P310	If swallowed: Immediately call a poison center/doctor.		
P321	Specific treatment (see on this label).		
P331	Do NOT induce vomiting.		
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.			
	Continue rinsing.		
P312	Call a poison center/doctor if you feel unwell.		
P362+P364	Take off contaminated clothing and wash it before reuse.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.		

#### P405

Store locked up. P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### - Other hazards

# - Results of PBT and vPvB assessment

- PBT: Not applicable.

P403+P235

- vPvB: Not applicable.

# 3 Composition/information on ingredients

## - Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

Store in a well-ventilated place. Keep cool.

- Dangerous	- Dangerous components:		
CAS: 142-82-5	heptane Flammable Liquids 2, H225; Aspiration Hazard 1, H304; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336	50 – 59%	
CAS: 67-63-0	isopropanol Flammable Liquids 2, H225; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	20 – 29%	
CAS: 34562-31-7	3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Skin Irritation 2, H315; Eye Irritation 2B, H320	10 – 19%	

# 4 First-aid measures

## - Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
  - Most important symptoms and effects, both acute and delayed No further relevant information available.
  - Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- Extinguishing media
  - Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
  - Protective equipment:

Wear self-contained respiratory protective device.

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

Wear fully protective suit.

(Contd. of page 2)

## 6 Accidental release measures

# - Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

# - Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

## - Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

#### - Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- Handling:

#### - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

## - Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

# - Conditions for safe storage, including any incompatibilities

- Storage:
  - Requirements to be met by storerooms and receptacles: No special requirements.
  - Information about storage in one common storage facility: Not required.
  - Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters
  - Components with limit values that require monitoring at the workplace:

At this time, the remaining constituent has no known exposure limits.

# CAS: 142-82-5 heptane PEL Long-term value: 2000 mg/m³, 500 ppm REL Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800\* mg/m³, 440\* ppm \*15-min TLV Short-term value: 500 ppm Long-term value: 400 ppm CAS: 67-63-0 isopropanol PEL Long-term value: 980 mg/m³, 400 ppm REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm TLV Short-term value: 400 ppm Long-term value: 200 ppm Long-term value: 200 ppm

# - Ingredients with biological limit values:

# CAS: 67-63-0 isopropanol

BEI 40 mg/L

BEI. A4

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- Additional information: The lists that were valid during the creation were used as basis.

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 3)

## - Exposure controls

## - Personal protective equipment:

## - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

## - Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

## - Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

## - Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

# 9 Physical and chemical properties

- General Information - Appearance:	
- Form:	Fluid
- Color:	According to product specification
- Odor:	Characteristic
- Odor threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
<ul> <li>Melting point/Melting range:</li> </ul>	Undetermined.
<ul> <li>Boiling point/Boiling range:</li> </ul>	≥ 82 °C (≥ 179.6 °F)
- Flash point:	-4 °C (24.8 °F)
- Flammability (solid, gaseous):	Highly flammable.
- Auto igniting:	215 °C (419 °F)
- Decomposition temperature:	Not determined.
- Ignition temperature:	Product is not selfigniting.
- Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- Explosion limits:	
- Lower:	1.1 Vol %
- Upper:	12 Vol %
- Vapor pressure at 20 °C (68 °F):	≤ 48 hPa (≤ 36 mm Hg)
- Vapor pressure at 50 °C (122 °F):	≤ 190 hPa (≤ 142.5 mm Hg)
Density at 20 °C (68 °F):	~ 0.75168 g/cm³ (~ 6.27277 lbs/gal)
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 4)

- Viscosity: - Dynamic: - Kinematic:	Not determined. Not determined.
- Solvent content: - Organic solvents: - VOC content:	85.0 % 84.98 % ~ 638.8 g/l / ~ 5.33 lb/gal
- Solids content:	0.0 %
- Other information	No further relevant information available.

# 10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
  - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

# - Information on toxicological effects

- Acute toxicity:

7.040	o comony	•	
- Li	D/LC50 v	alues that are relevant for classification:	
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	3,333 mg/kg	
Dermal	LD50	7,333 mg/kg	
CAS: 67-6	CAS: 67-63-0 isopropanol		
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/l (rat)	
CAS: 345	CAS: 34562-31-7 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine		
Oral	LD50	500 mg/kg (ATE)	
Dermal	LD50	1,100 mg/kg (ATE)	

- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)		
CAS: 67-63-0 isopropanol	3	
- NTP (National Toxicology Program)		
None of the ingredients is listed.		
- OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

# 12 Ecological information

- Toxicity
  - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
  - Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Remark: Very toxic for fish

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 5)

## - Additional ecological information:

## - General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

## - Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- Waste treatment methods
  - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
  - Recommendation: Disposal must be made according to official regulations.

# 14 Transport information - UN-Number - DOT, IMDG, IATA UN1993 - UN proper shipping name - DOT Flammable liquids, n.o.s. (Heptanes, Isopropanol) - IMDG FLAMMABLE LIQUID, N.O.S. (HEPTANES, ISOPROPANOL (ISOPROPYL ALCOHOL)), MARINE POLLUTANT - IATA FLAMMABLE LIQUID, N.O.S. (HEPTANES, ISOPROPANOL (ISOPROPYL ALCOHOL)) - Transport hazard class(es) - DOT - Class 3 Flammable liquids - Label - IMDG - Class 3 Flammable liquids - Label - IATA - Class 3 Flammable liquids - Label 3 - Packing group - DOT, IMDG, IATA Ш - Environmental hazards: Product contains environmentally hazardous substances: heptane - Marine pollutant: Symbol (fish and tree) - Special precautions for user Warning: Flammable liquids - Hazard identification number (Kemler code): 33 - EMS Number: F-E,S-E - Stowage Category В

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 6)

- Transport in bulk according to Annex II of MARPOL73/78  and the IBC Code  Not applicable	
and the IBC Code	Not applicable.
- Transport/Additional information:	
- DOT	
- Quantity limitations	On passenger aircraft/rail: 5 L
<b>4</b>	On cargo aircraft only: 60 L
- Remarks:	Special marking with the symbol (fish and tree).
- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: F2
=xooptou quamado (=q)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEPTANES,
<b>J</b>	ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, II,
	ENVIRONMENTALLY HAZARDOUS
	LIVINOIVIELI I IAZANDOOS

# 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
  - Sara

<ul> <li>Section 355 (extremely hazardous substances):</li> </ul>		
None of the ingredients is listed.		
- Section 313 (Specific toxic chemical listings):		
CAS: 67-63-0 isopropanol		
CAS: 1338-02-9 Metal Salt Complex		
- TSCA (Toxic Substances Control Act):		
heptane	ACTIVE	
isopropanol	ACTIVE	
3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	ACTIVE	
Metal Salt Complex	ACTIVE	
Distillates (petroleum), hydrotreated light	ACTIVI	
nonane	ACTIVI	
Naphthenic Acids	ACTIVI	
- Hazardous Air Pollutants		
None of the ingredients is listed.		
- Proposition 65		

None of the ingredients is listed. - Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Carcinogenic categories

- EPA (Environmental Protection Agency)	
CAS: 142-82-5 heptane	D
- TLV (Threshold Limit Value)	
CAS: 67-63-0 isopropanol	A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

<sup>-</sup> Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 01/23/2024 Reviewed on 01/23/2024

Trade name: Vibra-TITE® Excel Structural Activator

(Contd. of page 7)

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
- Classification System:
  - HMIS-ratings (scale 0 4)



- NFPA ratings (scale 0 - 4)



- Date of preparation / last revision 01/23/2024
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Oral 4: Acute toxicity - Category 4
Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Aspiration Hazard 1: Aspiration hazard – Category 1

- \* Data compared to the previous version altered.
- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.