

Safety Data Sheet
according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

1 Identification

- Product identifier

- **Trade name:** Vibra-TITE® Gasket Maker
- **Synonyms:** 709 Flexible Gasket Maker
- **Part number:** VT709
- **Application of the substance / the mixture**
 - Sealing
 - Sealant

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com

- Information department: Product Safety Department

- Emergency telephone number:

United States: 1-800-424-9300
International: +1-703-527-3887

*** 2 Hazard identification**

- Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity – Category 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure - Category 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irritation - Category 2

H315 Causes skin irritation.

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Skin Sensitizer - Category 1

H317 May cause an allergic skin reaction.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07 GHS08

- Signal word Warning

- Hazard-determining components of labeling:

Urethane methacrylate
dimethylbenzyl hydroperoxide
Cumene
methacrylic acid, monoester with propane-1,2-diol
2'-phenylacetohydrazide

- Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 1)

- Precautionary statements

| | |
|----------------|--|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P264 | Wash thoroughly after handling. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P280 | Wear protective gloves. |
| P302+P352 | If on skin: Wash with plenty of water. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P314 | Get medical advice/attention if you feel unwell. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |
| P332+P313 | If skin irritation occurs: Get medical advice/attention. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P321 | Specific treatment (see on this label). |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |

*** 3 Composition/Information on ingredients****- Chemical characterization: Mixtures****- Description:** Mixture of the substances listed below with nonhazardous additions.**- Dangerous components:**

| | | |
|-----------------|---|----------------|
| | Urethane methacrylate Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317 | 30 – 60% w/w |
| CAS: 27813-02-1 | methacrylic acid, monoester with propane-1,2-diol Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317 | 10 – 30% w/w |
| | Acrylic polymer Combustible Dusts - Category 1 | 5 – 10% w/w |
| CAS: 25852-47-5 | 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H335 | 1 – 5% w/w |
| CAS: 80-15-9 | dimethylbenzyl hydroperoxide Self-reactive Substances and Mixtures – Type F, H242; Organic Peroxides – Type E, H242; Acute Toxicity (Inhalation) - Category 3, H331; Specific Target Organ Toxicity - Repeated Exposure - Category 2, H373; Aspiration Hazard - Category 1, H304; Skin Corrosion - Category 1B, H314; Serious Eye Damage - Category 1, H318; Acute Toxicity (Oral) - Category 4, H302; Acute Toxicity (Dermal) – Category 4, H312; Specific Target Organ Toxicity - Single Exposure - Category 3, H335; Flammable Liquids - Category 4, H227 | 0.5 – 1.5% w/w |
| CAS: 114-83-0 | 2'-phenylacetohydrazide Acute Toxicity (Oral) - Category 4, H302; Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317; Specific Target Organ Toxicity - Single Exposure - Category 3, H335 | 0.1 – 1% w/w |
| CAS: 98-82-8 | Cumene Flammable Liquids - Category 3, H226; Carcinogenicity – Category 2, H351; Aspiration Hazard - Category 1, H304; Acute Toxicity (Oral) - Category 4, H302; Specific Target Organ Toxicity - Single Exposure - Category 3, H335 | 0.1 – 1% w/w |

4 First-aid measures**- Description of first aid measures****- After inhalation:**

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.**- After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.**- After swallowing:** If symptoms persist consult doctor.**- Information for doctor:****- Most important symptoms and effects, both acute and delayed** No further relevant information available.**- Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 2)

* 5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective clothing.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
 - **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/ Personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

CAS: 80-15-9 dimethylbenzyl hydroperoxide

| | |
|------------|--|
| WEEL (USA) | TWA: 6 mg/m ³ , 1 ppm Skin |
|------------|--|

CAS: 98-82-8 Cumene

| | |
|-------------|---|
| EL (Canada) | STEL: 75 ppm TWA: 25 ppm IARC 2B |
| EV (Canada) | TWA: 245 mg/m ³ , 50 ppm Skin |
| PEL (USA) | TWA: 245 mg/m ³ , 50 ppm Skin |
| REL (USA) | TWA: 245 mg/m ³ , 50 ppm Skin |
| TLV (USA) | TWA: 5 ppm A3 |

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
 - **Personal protective equipment:**
 - **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 3)

Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

* 9 Physical and chemical properties

| | |
|--|---|
| - Information on basic physical and chemical properties | |
| - General Information | |
| - Appearance: | |
| - Form: | Viscous |
| - Color: | Blue |
| - Odor: | Characteristic |
| - Odor threshold: | Not determined. |
| - pH-value: | Not determined. |
| - Change in condition | |
| - Melting point/Melting range: | Undetermined. |
| - Boiling point/Boiling range: | ≥ 209 °C |
| - Flash point: | 95 °C |
| - Flammability (solid, gaseous): | Not applicable. |
| - Decomposition temperature: | Not determined. |
| - Ignition temperature: | Product is not selfigniting. |
| - Danger of explosion: | Product does not present an explosion hazard. |
| - Explosion limits: | |
| - Lower: | Not determined. |
| - Upper: | Not determined. |
| - Vapor pressure at 20 °C: | ≤ 0.1 hPa |
| - Density: | |
| - Relative density | Not determined. |
| - Vapor density | Not determined. |
| - Evaporation rate | Not determined. |
| - Solubility in / Miscibility with | |
| - Water: | Not miscible or difficult to mix. |
| - Partition coefficient (n-octanol/water): | Not determined. |
| - Viscosity: | |
| - Dynamic at 20 °C: | 80,000 mPas |
| - Kinematic: | Not determined. |
| - Solvent content: | |
| - Organic solvents: | 0.7 % |
| - Water: | 0.2 % |
| - VOC content: | 0.71 % |
| | 7.1 g/l / 0.06 lb/gal |

(Contd. on page 5)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 4)

| | |
|----------------------------|--|
| - Solids content: | 19.0 % |
| - Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

| - LD/LC50 values that are relevant for classification: | | |
|---|----------|-----------------------|
| ATE (Acute Toxicity Estimate) | | |
| Oral | LD50 | 30,317 mg/kg (rat) |
| Dermal | LD50 | 39,683 mg/kg (rat) |
| Inhalative | LC50/4 h | 17,460 mg/l (rat) |
| CAS: 80-15-9 dimethylbenzyl hydroperoxide | | |
| Oral | LD50 | 382 mg/kg (rat) |
| Dermal | LD50 | 500 mg/kg (rat) |
| Inhalative | LC50/4 h | 220 mg/l (rat) |
| CAS: 114-83-0 2'-phenylacetohydrazide | | |
| Oral | LD50 | 270 mg/kg (mouse) |
| CAS: 98-82-8 Cumene | | |
| Oral | LD50 | 1,400 mg/kg (rat) |
| Dermal | LD50 | 12,300 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 24.7 mg/l (mouse) |

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

| - IARC (International Agency for Research on Cancer) | | |
|---|--------------------|----|
| CAS: 98-82-8 | Cumene | 2B |
| CAS: 91-20-3 | naphthalene | 2B |
| CAS: 1330-20-7 | Mixed Xylenes | 3 |
| CAS: 100-41-4 | ethylbenzene | 2B |
| - NTP (National Toxicology Program) | | |
| CAS: 98-82-8 | Cumene | R |
| CAS: 130-15-4 | 1,4-naphthoquinone | R |
| CAS: 91-20-3 | naphthalene | R |

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 5)

- Additional ecological information:**- General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment**- PBT:** Not applicable.**- vPvB:** Not applicable.**- Other adverse effects** No further relevant information available.**13 Disposal considerations****- Waste treatment methods****- Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**- Uncleaned packagings:****- Recommendation:** Disposal must be made according to official regulations.**14 Transport information****- UN-Number****- DOT/TDG, ADR, ADN, IMDG, IATA** not regulated**- UN proper shipping name****- DOT/TDG, ADR, ADN, IMDG, IATA** not regulated**- Transport hazard class(es)****- DOT/TDG, ADR, ADN, IMDG, IATA**
- Class not regulated**- Packing group****- DOT/TDG, ADR, IMDG, IATA** not regulated**- Environmental hazards:****- Marine pollutant:** No**- Special precautions for user**

Not applicable.

- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

- UN "Model Regulation":

not regulated

15 Regulatory information*- Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

- Sara**- Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

CAS: 80-15-9 dimethylbenzyl hydroperoxide

CAS: 98-82-8 Cumene

CAS: 91-20-3 naphthalene

Rheology Additive

CAS: 1330-20-7 Mixed Xylenes

CAS: 100-41-4 ethylbenzene

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Canadian substance listings:**- Canadian Domestic Substances List (DSL)**

CAS: 27813-02-1 methacrylic acid, monoester with propane-1,2-diol

Acrylic polymer

CAS: 25852-47-5 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate

CAS: 67762-90-7 Amorphous Silica

CAS: 80-15-9 dimethylbenzyl hydroperoxide

CAS: 128-44-9 Saccharin

(Contd. on page 7)

Safety Data Sheet

according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 6)

| | |
|-----------------|--|
| CAS: 57-55-6 | propane-1,2-diol |
| CAS: 114-83-0 | 2'-phenylacetohydrazide |
| CAS: 7732-18-5 | Deionized water |
| CAS: 98-82-8 | Cumene |
| CAS: 617-94-7 | 2-Phenyl-2-propanol |
| CAS: 71819-49-3 | C.I. Solvent Blue 98 |
| CAS: 64742-94-5 | Solvent naphtha (petroleum), heavy arom. |
| CAS: 64-02-8 | tetrasodium ethylenediaminetetraacetate |
| CAS: 18268-70-7 | Tetraethylene glycol hexoate |
| CAS: 2809-21-4 | 1-hydroxyethane-1,1-diylbis(phosphonic acid) |
| CAS: 64742-53-6 | Distillates (petroleum), hydrotreated light naphthenic |
| CAS: 74499-36-8 | Colorant |
| CAS: 5080-22-8 | N-isopropylhydroxylamine |
| CAS: 130-15-4 | 1,4-naphthoquinone |
| CAS: 7128-64-5 | 2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole) |
| CAS: 91-20-3 | naphthalene |
| CAS: 13598-36-2 | phosphorous acid |
| | Rheology Additive |
| CAS: 1330-20-7 | Mixed Xylenes |
| CAS: 100-41-4 | ethylbenzene |

- Canadian Non-Domestic Substances List (NDSL)

CAS: 127-06-0 | 2-Propanone, oxime

- Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

- Canadian Ingredient Disclosure list (limit 1%)

CAS: 80-15-9 | dimethylbenzyl hydroperoxide

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affairs

- Contact: Safety, Health and Environmental Affairs

- Classification System:

- HMIS-ratings (scale 0 - 4)

| | | |
|------------|---|----------------|
| HEALTH | 2 | Health = *2 |
| FIRE | 1 | Fire = 1 |
| REACTIVITY | 0 | Reactivity = 0 |

- NFPA ratings (scale 0 - 4)

| | | | |
|---|---|---|----------------|
| 2 | 1 | 0 | Health = 2 |
| | | | Fire = 1 |
| | | | Reactivity = 0 |

- Date of the latest revision of the safety data sheet 01/29/2024

- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

©ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
 ®Vibra-TITE is a registered trademark of ND Industries, Inc.

(Contd. on page 8)

Safety Data Sheet
according to HPR, Schedule 1

Printing date 01/29/2024

Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 7)