

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

1 Identification

- Product identifier

- **Trade name:** Vibra-TITE® Gasket Maker
- **Synonyms:** 709 Flexible Gasket Maker
- **Part number:** VT709
- **Application of the substance / the mixture**
 - Sealing
 - Sealant

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com

- **Information department:** Product Safety Department

- Emergency telephone number:

United States: 1-800-424-9300
International: +1-703-527-3887

*** 2 Hazard(s) identification**

- Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure 2

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07 GHS08

- **Signal word** Warning

- Hazard-determining components of labeling:

Urethane methacrylate
dimethylbenzyl hydroperoxide
Cumene
methacrylic acid, monoester with propane-1,2-diol
2'-phenylacetohydrazide

- Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P201 Obtain special instructions before use.

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 1)

P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P302+P352	If on skin: Wash with plenty of water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P321	Specific treatment (see on this label).
P337+P313	If eye irritation persists: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

	Urethane methacrylate Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317	50 – 59%
CAS: 27813-02-1	methacrylic acid, monoester with propane-1,2-diol Eye Irritation 2A, H319; Sensitization - Skin 1, H317	20 – 29%
	Acrylic polymer Combustible Dust	9.38%
CAS: 25852-47-5	2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	4.94%
CAS: 80-15-9	dimethylbenzyl hydroperoxide Self-reactive substances and mixtures - Type F, H242; Organic Peroxides - Type E, H242; Acute Toxicity - Inhalation 3, H331; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304; Skin Corrosion 1B, H314; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Specific Target Organ Toxicity - Single Exposure 3, H335; Flammable Liquids 4, H227	1 – 4%
CAS: 114-83-0	2'-phenylacetohydrazide Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Eye Irritation 2A, H319; Sensitization - Skin 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	≤ 1%
CAS: 98-82-8	Cumene Flammable Liquids 3, H226; Carcinogenicity 2, H351; Aspiration Hazard 1, H304; Acute Toxicity - Oral 4, H302; Specific Target Organ Toxicity - Single Exposure 3, H335	≤ 1%

4 First-aid measures

- Description of first aid measures**- After inhalation:**

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective clothing.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
 - **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
At this time, the other constituents have no known exposure limits.

CAS: 80-15-9 dimethylbenzyl hydroperoxide

WEEL	Long-term value: 6 mg/m ³ , 1 ppm Skin
------	--

CAS: 98-82-8 Cumene

PEL	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV	Long-term value: 5 ppm A3

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
 - **Personal protective equipment:**
 - **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
 - **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 3)

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties	
- General Information	
- Appearance:	
- Form:	Viscous
- Color:	Blue
- Odor:	Characteristic
- Odor threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	≥ 209 °C (≥ 408.2 °F)
- Flash point:	95 °C (203 °F)
- Flammability (solid, gaseous):	Not applicable.
- Decomposition temperature:	Not determined.
- Ignition temperature:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits:	
- Lower:	Not determined.
- Upper:	Not determined.
- Vapor pressure at 20 °C (68 °F):	≤ 0.1 hPa
- Density:	
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water): Not determined.	
- Viscosity:	
- Dynamic at 20 °C (68 °F):	80,000 mPas
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	0.7 %
- Water:	0.2 %
- VOC content:	0.71 %
	7.1 g/l / 0.06 lb/gal
- Solids content:	19.0 %
- Other information	No further relevant information available.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 4)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	30,317 mg/kg (rat)
Dermal	LD50	39,683 mg/kg (rat)
Inhalative	LC50/4 h	17,460 mg/l (rat)

CAS: 80-15-9 dimethylbenzyl hydroperoxide

Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)

CAS: 114-83-0 2'-phenylacetohydrazide

Oral	LD50	270 mg/kg (mouse)
------	------	-------------------

CAS: 98-82-8 Cumene

Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- Sensitization: Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

CAS: 98-82-8	Cumene	2B
CAS: 91-20-3	naphthalene	2B
CAS: 1330-20-7	Mixed Xylenes	3
CAS: 100-41-4	ethylbenzene	2B

- NTP (National Toxicology Program)

CAS: 98-82-8	Cumene	R
CAS: 130-15-4	1,4-naphthoquinone	R
CAS: 91-20-3	naphthalene	R

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**

- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 5)

- Results of PBT and vPvB assessment- **PBT:** Not applicable.- **vPvB:** Not applicable.- **Other adverse effects** No further relevant information available.**13 Disposal considerations****- Waste treatment methods**- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**- Uncleaned packagings:**- **Recommendation:** Disposal must be made according to official regulations.**14 Transport information**

- UN-Number	
- DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name	
- DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA	
- Class	not regulated
- Packing group	
- DOT, IMDG, IATA	not regulated
- Environmental hazards:	
- Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- UN "Model Regulation":	not regulated

15 Regulatory information**- Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

- Sara**- Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

CAS: 80-15-9	dimethylbenzyl hydroperoxide
CAS: 98-82-8	Cumene
CAS: 91-20-3	naphthalene
	Rheology Additive
CAS: 1330-20-7	Mixed Xylenes
CAS: 100-41-4	ethylbenzene

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants

CAS: 98-82-8	Cumene
CAS: 130-15-4	1,4-naphthoquinone
CAS: 91-20-3	naphthalene
CAS: 1330-20-7	Mixed Xylenes
CAS: 100-41-4	ethylbenzene

- Proposition 65**- Chemicals known to cause cancer:**

CAS: 98-82-8	Cumene
CAS: 91-20-3	naphthalene
	Carbon Black Preparation

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 6)

CAS: 100-41-4	ethylbenzene	
- Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
- Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
- Chemicals known to cause developmental toxicity:		
Rheology Additive		
- Carcinogenic categories		
- EPA (Environmental Protection Agency)		
CAS: 98-82-8	Cumene	D, CBD
CAS: 91-20-3	naphthalene	C, CBD
CAS: 1330-20-7	Mixed Xylenes	I
CAS: 100-41-4	ethylbenzene	D
- TLV (Threshold Limit Value)		
CAS: 91-20-3	naphthalene	A4
CAS: 1330-20-7	Mixed Xylenes	A4
CAS: 100-41-4	ethylbenzene	A3
- NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs
- **Contact:** Safety, Health and Environmental Affairs
- **Classification System:**

- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **NFPA ratings (scale 0 - 4)**

1	2	0	Health = 2
			Fire = 1
			Reactivity = 0

- **Date of preparation / last revision** 01/23/2024

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids – Category 4

Self-reactive substances and mixtures - Type F: Self-reactive substances and mixtures – Type E/F

Organic Peroxides - Type E: Organic peroxides – Type E/F

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Acute Toxicity - Inhalation 3: Acute toxicity – Category 3

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 7)

Aspiration Hazard 1: Aspiration hazard – Category 1

- * **Data compared to the previous version altered.**

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,

®Vibra-TITE is a registered trademark of ND Industries, Inc.