



Page 1/7

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/29/2024 Reviewed on 01/29/2024

1 Identification

- Product identifier

- Trade name: Vibra-TITE® Gasket Maker

- Synonyms: 710 High Temperature Rigid Flange Sealant

- Part number: VT710

- Application of the substance / the mixture

Sealing Sealant

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department

- Emergency telephone number: United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard identification

- Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity – Category 2 H351 Suspected of causing cancer.



Skin Irritation - Category 2 Eye Irritation - Category 2A Skin Sensitizer - Category 1 H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - Category 3 H335 May cause respiratory irritation.

- Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms





GHS07 GHS08

- Signal word Warning

- Hazard-determining components of labeling:

Urethane methacrylate

2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate

Cumene

Bisphenol A epoxy Acrylate

2'-phenylacetohydrazide

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

- Precautionary statements

P201 Obtain special instructions before use.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 1) P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection. P280 Wear protective gloves. P302+P352 If on skin: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P312 Call a poison center/doctor if you feel unwell. P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P321 Specific treatment (see on this label). P337+P313 If eye irritation persists: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/Information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

| - Dangerous | components: | |
|-----------------|--|--------------|
| CAS: 25852-47-5 | 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Specific Target Organ Toxicity - Single Exposure - Category 3, H335 | 15 – 40% w/v |
| | Urethane methacrylate Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317 | 10 – 30% w/v |
| | Bisphenol A epoxy Acrylate Skin Sensitizer - Category 1, H317 | 5 – 10% w/w |
| | Acrylic polymer Combustible Dusts - Category 1 | 5 – 10% w/w |
| | Acrylic polymer Combustible Dusts - Category 1 | 5 – 10% w/w |
| CAS: 80-15-9 | dimethylbenzyl hydroperoxide Self-reactive Substances and Mixtures – Type F, H242; Organic Peroxides – Type E, H242; Acute Toxicity (Inhalation) - Category 3, H331; Specific Target Organ Toxicity - Repeated Exposure - Category 2, H373; Aspiration Hazard - Category 1, H304; Skin Corrosion - Category 1B, H314; Serious Eye Damage - Category 1, H318; Acute Toxicity (Oral) - Category 4, H302; Acute Toxicity (Dermal) – Category 4, H312; Specific Target Organ Toxicity - Single Exposure - Category 3, H335; Flammable Liquids - Category 4, H227 | 0.1 – 1% w/v |
| CAS: 114-83-0 | 2'-phenylacetohydrazide Acute Toxicity (Oral) - Category 4, H302; Skin Irritation - Category 2, H315; Eye Irritation - Category 2A, H319; Skin Sensitizer - Category 1, H317; Specific Target Organ Toxicity - Single Exposure - Category 3, H335 | 0.1 – 1% w/v |
| CAS: 98-82-8 | Cumene Flammable Liquids - Category 3, H226; Carcinogenicity – Category 2, H351; Aspiration Hazard - Category 1, H304; Acute Toxicity (Oral) - Category 4, H302; Specific Target Organ Toxicity - Single Exposure - Category 3, H335 | ≤ 0.1% w/w |

4 First-aid measures

- Description of first aid measures

- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 2)

Indication of any immediate medical attention and special treatment needed
 No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 - Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
 - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
 - Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

| At this tim | ie, the other constituents have no known exposure limits. |
|--------------|---|
| CAS: 80-15-9 | dimethylbenzyl hydroperoxide |
| WEEL (USA) | TWA: 6 mg/m³, 1 ppm Skin |
| CAS: 98-82-8 | Cumene |
| EL (Canada) | STEL: 75 ppm TWA: 25 ppm IARC 2B |
| EV (Canada) | TWA: 245 mg/m³, 50 ppm Skin |
| PEL (USA) | TWA: 245 mg/m³, 50 ppm Skin |
| REL (USA) | TWA: 245 mg/m³, 50 ppm Skin |
| TLV (USA) | TWA: 5 ppm A3 |

⁻ Additional information: The lists that were valid during the creation were used as basis.

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 3)

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

9 Physical and chemical properties

| - Information on basic physical and chemical properties | | |
|--|---|--|
| - General Information | | |
| - Appearance: | | |
| - Form: | Viscous | |
| - Color: | Pink | |
| - Odor: | Characteristic | |
| - Odor threshold: | Not determined. | |
| - pH-value: | Not determined. | |
| - Change in condition | | |
| - Melting point/Melting range: | Undetermined. | |
| - Boiling point/Boiling range: | ≥ 200 °C | |
| - Flash point: | 100 °C | |
| - Flammability (solid, gaseous): | Not applicable. | |
| - Auto igniting: | n.a. °C | |
| - Decomposition temperature: | Not determined. | |
| - Ignition temperature: | Product is not selfigniting. | |
| - Danger of explosion: | Product does not present an explosion hazard. | |
| - Explosion limits: | | |
| - Lower: | Not determined. | |
| - Upper: | Not determined. | |
| - Vapor pressure: | Not determined. | |
| - Density: | Not determined. | |
| - Relative density | Not determined. Not determined. | |
| - Vapor density | Not determined. | |
| - Evaporation rate | Not determined. | |
| • | Not determined. | |
| Solubility in / Miscibility with Water: | Not miscible or difficult to mix. | |
| - Partition coefficient (n-octanol/wate | er): Not determined. | |
| - Viscosity: | | |
| - Dynamic at 20 °C: | 100,000 mPas | |

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 4)

| - Kinematic: | Not determined. |
|-------------------------------------|--|
| - Solvent content: | |
| Organic solvents: | 0.7 % |
| - Water: | 0.8 % |
| VOC content: | 0.69 % |
| | 6.9 g/l / 0.06 lb/gal |
| - Solids content: | 52.0 % |
| Other information | No further relevant information available. |

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

| - LE | - LD/LC50 values that are relevant for classification: | |
|------------|--|-------------------------|
| ATE (Acut | e Toxicity | r Estimate) |
| Inhalative | LC50/4 h | 26,190 mg/l (rat) |
| CAS: 80-1 | 5-9 dimet | hylbenzyl hydroperoxide |
| Oral | LD50 | 382 mg/kg (rat) |
| Dermal | LD50 | 500 mg/kg (rat) |
| Inhalative | LC50/4 h | 220 mg/l (rat) |
| CAS: 114- | 83-0 2'-ph | nenylacetohydrazide |
| Oral | LD50 | 270 mg/kg (mouse) |
| CAS: 98-8 | CAS: 98-82-8 Cumene | |
| Oral | LD50 | 1,400 mg/kg (rat) |
| Dermal | LD50 | 12,300 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 24.7 mg/l (mouse) |

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- Carcinogenic categories

| (International Agency for Research on Cancer) | |
|---|---|
| Cumene | 2B |
| titanium dioxide | 2B |
| 2-butoxyethanol | 3 |
| (National Toxicology Program) | |
| umene | R |
| ,4-naphthoquinone | R |
| | C (International Agency for Research on Cancer) Cumene titanium dioxide 2-butoxyethanol (National Toxicology Program) Cumene ,4-naphthoquinone |

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.

(Contd. of page 5)

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

- Additional ecological information:

- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - **PBT:** Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

| 14 Transport information | | |
|---|----------------------------|--|
| - UN-Number - DOT/TDG, ADR, IMDG, IATA | not regulated | |
| - UN proper shipping name - DOT/TDG, ADR, IMDG, IATA | not regulated | |
| - Transport hazard class(es) | | |
| - DOT/TDG, ADR, ADN, IMDG, IATA - Class | not regulated | |
| - Packing group - DOT/TDG, ADR, IMDG, IATA | not regulated | |
| - Environmental hazards: - Marine pollutant: | No | |
| - Special precautions for user | Not applicable. | |
| - Transport in bulk according to Annex II of MAI and the IBC Code | RPOL73/78 Not applicable. | |
| - UN "Model Regulation": | not regulated | |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 - Sara

| - Se | - Section 355 (extremely hazardous substances): | |
|-----------------|---|--|
| None of the ing | redients is listed. | |
| - Se | - Section 313 (Specific toxic chemical listings): | |
| CAS: 80-15-9 | dimethylbenzyl hydroperoxide | |
| CAS: 98-82-8 | Cumene | |
| CAS: 98-86-2 | acetophenone | |
| CAS: 111-76-2 | 2-butoxyethanol | |
| - TSCA | - TSCA (Toxic Substances Control Act): | |
| All components | All components have the value ACTIVE. | |

- Canadian substance listings:

| • | | |
|---|--|--|
| - Canad | - Canadian Domestic Substances List (DSL) | |
| CAS: 25852-47-5 | 2-(2-methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate | |
| CAS: 9004-96-0 | Polyethylene Glycol 200 Monooleate | |
| | Bisphenol A epoxy Acrylate | |
| | Acrylic polymer | |
| | Acrylic polymer | |
| CAS: 67762-90-7 | Amorphous Silica | |
| CAS: 128-44-9 | Saccharin | |
| CAS: 80-15-9 | dimethylbenzyl hydroperoxide | |
| | (O-mtd 7) | |

Printing date 01/29/2024 Reviewed on 01/29/2024

Trade name: Vibra-TITE® Gasket Maker

| 040 7700 40 5 | (Contd. of page | |
|---------------------|---|--|
| CAS: 7732-18-5 | Deionized water | |
| CAS: 57-55-6 | propane-1,2-diol | |
| CAS: 114-83-0 | 2'-phenylacetohydrazide | |
| CAS: 98-82-8 | Cumene | |
| | Pigment | |
| CAS: 7128-64-5 | 2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole) | |
| CAS: 64-02-8 | tetrasodium ethylenediaminetetraacetate | |
| CAS: 5080-22-8 | N-isopropylhydroxylamine | |
| CAS: 13463-67-7 | titanium dioxide | |
| CAS: 98-86-2 | acetophenone | |
| CAS: 617-94-7 | 2-Phenyl-2-propanol | |
| CAS: 2809-21-4 | 1-hydroxyethane-1,1-diylbis(phosphonic acid) | |
| CAS: 130-15-4 | 1,4-naphthoquinone | |
| CAS: 112945-52-5 | Silicon dioxide, amorphous | |
| CAS: 3068-39-1 | 3,6-bis(ethylamino)-9-[2-(methoxycarbonyl)phenyl]-2,7-dimethylxanthylium chloride | |
| CAS: 13598-36-2 | phosphorous acid | |
| CAS: 21645-51-2 | Alumina Trihydrate | |
| CAS: 111-76-2 | 2-butoxyethanol | |
| CAS: 126-86-3 | 2,4,7,9-tetramethyldec-5-yne-4,7-diol | |
| - Canad | dian Non-Domestic Substances List (NDSL) | |
| CAS: 127-06-0 2-F | Propanone, oxime | |
| - Canad | dian Ingredient Disclosure list (limit 0.1%) | |
| None of the ingredi | ents is listed. | |
| - Canad | - Canadian Ingredient Disclosure list (limit 1%) | |
| None of the ingredi | ents is listed. | |
| | | |

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
- Classification System:
 - HMIS-ratings (scale 0 4)



- NFPA ratings (scale 0 - 4)



- Date of the latest revision of the safety data sheet 01/29/2024
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.