



Safety Data Sheet

acc. to OSHA HCS

Printing date 01/23/2024

1 Identification

- Product identifier

- Trade name: Vibra-TITE® Gasket Maker
 - Synonyms: 993 RTV Silicone Gasket Maker Black
 - **Part number:** VT993
 - Application of the substance / the mixture Sealing
 - Sealant

- Details of the supplier of the safety data sheet

- *Manufacturer/Supplier:* ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department

- *Emergency telephone number:* United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture

GHS08 Health hazard

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irritation 2 Sensitization - Skin 1 H315 Causes skin irritation. H317 May cause an allergic skin reaction.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS). - **Hazard pictograms**



- Signal word Warning

- Hazard-determining components of labeling: Oximino Silane
- Hazard statements
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves.
- P302+P352 If on skin: Wash with plenty of water.
- P314 Get medical advice/attention if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Page 1/7

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

- P321 Specific treatment (see on this label).
- P363 Wash contaminated clothing before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous components 	:
--	---

Dungerous	components.	
CAS: 1317-65-3	Calcium Carbonate	40 – 49%
	Skin Irritation 2, H315	
CAS: 34036-80-1	Oximino Silane	10 – 19%
	Specific Target Organ Toxicity - Repeated Exposure 2, H373; Sensitization - Skin 1, H317	
CAS: 22984-54-9	butan-2-one O,O',O"-(methylsilylidyne)trioxime	4.50%
	Acute Toxicity - Dermal 3, H311	
CAS: 1333-86-4	Carbon black	≤ 1%
	Self-heating substances and mixtures 2, H252; Carcinogenicity 2, H351	

4 First-aid measures

- Description of first aid measures

- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. - After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available. - Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters

- Protective equipment:

- Wear self-contained respiratory protective device.
- Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation Wear protective clothing.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- Dispose of the collected material according to regulations.
- Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Printing date 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 2)

Reviewed on 01/23/2024

7 Handling and storage

- Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.

- Control parameters

- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

CAS: 1333-86-4 Carbon black

- PEL Long-term value: 3.5 mg/m³
- REL Long-term value: 3.5* mg/m³

*0.1 in presence of PAHs;See Pocket Guide Apps.A+C

- TLV Long-term value: 3* mg/m³
- *inhalable fraction, A3

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work. Avoid contact with the skin.

Avoid contact with the eyes and skin.

Protective gloves

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber. NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and - General Information - Appearance:	l chemical properties	
- Form:	Pasty	
- Color:	Black	
- Odor:	Light	
- Odor threshold:	Not determined.	

Printing date 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

Reviewed on 01/23/2024

	(Contd. of
- pH-value:	Not determined.
- Change in condition - Melting point/Melting range: - Boiling point/Boiling range:	
- Flash point:	> 95 °C (> 203 °F)
- Flammability (solid, gaseous):	Not applicable.
- Auto igniting:	> 370 °C (> 698 °F)
- Decomposition temperature	: Not determined.
- Ignition temperature:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits: - Lower: - Upper:	Not determined. Not determined.
- Vapor pressure:	Not determined.
- Density at 20 °C (68 °F): - Relative density - Vapor density - Evaporation rate	~ 1.04 g/cm³ (~ 8.6788 lbs/gal) Not determined. Not determined. Not determined.
- Solubility in / Miscibility with - Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/	<i>water):</i> Not determined.
- Viscosity: - Dynamic: - Kinematic:	Not determined. Not determined.
- Solvent content: - VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
- Solids content:	55.5 %
Other information	No further relevant information available.

- Reactivity No further relevant information available.

- Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

	- LD/LC50 values that are relevant for classification:
Oral	LD50 5,000 mg/kg (rat)
CAS:	22984-54-9 butan-2-one O,O',O''-(methylsilylidyne)trioxime
Derm	al LD50 300 mg/kg (ATE)
CAS:	1333-86-4 Carbon black
Oral	LD50 10,000 mg/kg (rat)
	- Primary irritant effect:
	- on the skin: Irritant to skin and mucous membranes.

- on the eye: No irritating effect.

- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Printing date 01/23/2024

· ··· -1-+ 1 / - - -Tr

Frade name: Vibra-TITE® Gasket Maker	
Irritant	(Contd. of page 4
- Carcinogenic categories	
- IARC (International Agency for Re	search on Cancer)
CAS: 1333-86-4 Carbon black	2B
- NTP (National Toxicology Program	n)
None of the ingredients is listed.	·
- OSHA-Ca (Occupational Safety &	Health Administration)
None of the ingredients is listed.	
2 Ecological information	
- Toxicity	
- Aquatic toxicity: No further relevant information	
- Persistence and degradability No further releva	ant information available.
- Behavior in environmental systems: - Bioaccumulative potential No further releva	nt information quallable
- Mobility in soil No further relevant information	
- Additional ecological information:	
- General notes:	
Water hazard class 1 (Self-assessment): slightly	hazardous for water s of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment	of it to reach ground water, water course of sewage system.
- PBT: Not applicable.	
- vPvB: Not applicable.	
- Other adverse effects No further relevant information	ation available.
3 Disposal considerations	
- Waste treatment methods	
- Recommendation: Must not be disposed of to	ogether with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:	
- Recommendation: Disposal must be made ad	ccording to official regulations.
4 Transport information	
- UN-Number	
- DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name - DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA	
- Class	not regulated
- Packing group	

- Packing group - DOT, IMDG, IATA	not regulated
- Environmental hazards: - Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	
- UN "Model Regulation":	not regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. of page 5)

Reviewed on 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

- Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
- TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
- Hazardous Air Pollutants	
None of the ingredients is listed.	
- Proposition 65	
- Chemicals known to cause cancer:	
None of the ingredients is listed.	
 Chemicals known to cause reproductive toxicity for females: 	
None of the ingredients is listed.	
- Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
- Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
- Carcinogenic categories	
- EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
- TLV (Threshold Limit Value)	
CAS: 1333-86-4 Carbon black	A4
- NIOSH-Ca (National Institute for Occupational Safety and Health)	

CAS: 1333-86-4 Carbon black

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
- Classification System:

- HMIS-ratings (scale 0 - 4)



- NFPA ratings (scale 0 - 4)



- Date of preparation / last revision 01/23/2024

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

- vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit Self-heating substances and mixtures 2: Self-heating substances and mixtures Category 2
- Acute Toxicity Dermal 3: Acute toxicity Category 3 Skin Irritation 2: Skin corrosion/irritation Category 2

Sensitization - Skin 1: Skin sensitisation – Category 1 Carcinogenicity 2: Carcinogenicity – Category 2 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

- * Data compared to the previous version altered.

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 6)

Reviewed on 01/23/2024

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.