



Page 1/7

Safety Data Sheet acc. to OSHA HCS

Printing date 01/23/2024 Reviewed on 04/05/2023

1 Identification

- Product identifier

- Trade name: Vibra-TITE® Gasket Maker

- Synonyms: 998 RTV Silicone Gasket Maker - Black

- Part number: VT998

- Application of the substance / the mixture

Sealing Sealant

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017 USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product Safety Department
- Emergency telephone number: United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 - Hazard pictograms



GHS07

- Signal word Warning

- Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

- Precautionary statements

P264 Wash thoroughly after handling.
P280 Wear eye protection / face protection.
P302+P352 If on skin: Wash with plenty of water.
Specific treatment (see on this label).

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P337+P313 If eye irritation persists: Get medical advice/attention.

- Other hazards

- Results of PBT and vPvB assessment

- Results C	TPBT and VPVB assessment
- PBT:	
CAS: 556-67-2	octamethylcyclotetrasiloxane
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
- vPvB	
CAS: 556-67-2	octamethylcyclotetrasiloxane
	(Contd. on page 2)

Printing date 01/23/2024 Reviewed on 04/05/2023

Trade name: Vibra-TITE® Gasket Maker

CAS: 541-02-6 | 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

(Contd. of page 1)

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 4253-34-3	methylsilanetriyl triacetate	1 – 4%
	Eye Irritation 2B, H320	
CAS: 17689-77-9	Ethyltriacetoxysilane	1 – 4%
	Skin Corrosion 1C, H314; Eye Damage 1, H318; Acute Toxicity - Oral 4, H302	
CAS: 556-67-2	octamethylcyclotetrasiloxane	≤ 1%
	Flammable Liquids 3, H226; Toxic to Reproduction 2, H361 PBT; vPvB	
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane PBT; vPvB	≤ 1%

4 First-aid measures

- Description of first aid measures

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.

- Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep receptacle tightly sealed.

Printing date 01/23/2024 Reviewed on 04/05/2023

Trade name: Vibra-TITE® Gasket Maker

- Specific end use(s) No further relevant information available.

(Contd. of page 2)

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- Control parameters
 - Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

CAS: 556-67-2 octamethylcyclotetrasiloxane

WEEL Long-term value: 10* ppm

*OARS WEEL

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls
 - Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Body protection: Protective work clothing

9 Physical and chemical properties

- Appearance:		
- Form:	Pasty	
- Color:	Black	
- Odor:	Light	
- Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	6	
Change in condition		
 Melting point/Melting range: 	Undetermined.	
 Boiling point/Boiling range: 	Undetermined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Auto igniting:	> 370 °C (> 698 °F)	
- Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
- Explosion limits:		
- Lower:	Not determined.	

Printing date 01/23/2024 Reviewed on 04/05/2023

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 3)

- Upper:	Not determined.	
- Vapor pressure:	Not determined.	
- Density at 20 °C (68 °F):	≥ 1.10161 - ≤ 1.10167 g/cm³ (≥ 9.19294 - ≤ 9.19344 lbs/gal)	
- Relative density	Not determined.	
- Vapor density	Not determined.	
- Evaporation rate	Not determined.	
- Solubility in / Miscibility with		
- Water:	Not miscible or difficult to mix.	
- Partition coefficient (n-octanol/water): Not determined.		
- Viscosity:		
- Dynamic:	Not determined.	
- Kinematic:	Not determined.	
- Solvent content:		
- Organic solvents:	0.1 %	
- VOC content:	0.10 %	
	1.1 g/l / 0.01 lb/gal	
- Solids content:	12.1 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:
 - LD/LC50 values that are relevant for classification:

Oral LD50 5,000 mg/kg (rat)

CAS: 17689-77-9 Ethyltriacetoxysilane

Oral LD50 500 mg/kg (ATE)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Carcinogenic categories

• • • • • • • • • • • • • • • • • • • •	iogomo outogonos	
- IAR	RC (International Agency for Research on Cancer)	
CAS: 1333-86-4	4 Carbon black	2B
CAS: 13463-67-	titanium dioxide	2B
- NTI	P (National Toxicology Program)	
None of the ingr	redients is listed.	
- OS	SHA-Ca (Occupational Safety & Health Administration)	
None of the ingr	redients is listed.	

12 Ecological information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.

Printing date 01/23/2024 Reviewed on 04/05/2023

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 4)

- Behavior in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.
- Additional ecological information:
 - General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment

- PBT:		
CAS: 556-67-2	octamethylcyclotetrasiloxane	
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	
- vPvB:		
CAS: 556-67-2	octamethylcyclotetrasiloxane	
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	
- Other adverse effects No further relevant information available.		

13 Disposal considerations

- Waste treatment methods
 - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 - Recommendation: Disposal must be made according to official regulations.

14 Transport information	
- UN-Number - DOT, ADN, IMDG, IATA	not regulated
- UN proper shipping name - DOT, ADN, IMDG, IATA	not regulated
- Transport hazard class(es)	
- DOT, ADN, IMDG, IATA - Class	not regulated
- Packing group - DOT, IMDG, IATA	not regulated
- Environmental hazards: - Marine pollutant:	No
- Special precautions for user	Not applicable.
- Transport in bulk according to Annex II of and the IBC Code	of MARPOL73/78 Not applicable.
- UN "Model Regulation":	not regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 - Sara

- Sara	
- Section 355 (extremely hazardous substances	s):
None of the ingredients is listed.	
- Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
- TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
- Hazardous Air Pollutants	

None of the ingredients is listed.

- Proposition 65
 - Chemicals known to cause cancer:

CAS: 13463-67-7 titanium dioxide

Printing date 01/23/2024 Reviewed on 04/05/2023

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 5) - Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. - Chemicals known to cause developmental toxicity: None of the ingredients is listed.

- Carcinogenic categories

- EPA	(Environmental Protection Agency)	
None of the ingred	dients is listed.	
- TLV	(Threshold Limit Value)	
CAS: 1333-86-4	Carbon black	A4
CAS: 1067-33-0	dibutyltin di(acetate)	A4
CAS: 13463-67-7	titanium dioxide	A4
- NIOS	H-Ca (National Institute for Occupational Safety and Health)	
CAS: 1333-86-4	Carbon black	
CAS: 13463-67-7	titanium dioxide	
	t.	

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- Contact: Safety, Health and Environmental Affaires
- Classification System:
 - HMIS-ratings (scale 0 4)



Fire = 1

REACTIVITY Reactivity = 0

- NFPA ratings (scale 0 - 4)



- Date of preparation / last revision 01/23/2024

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by

Road)
IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 4: Acute toxicity - Category 4
Skin Corrosion 1C: Skin corrosion/irritation - Category 1C

Skin Irritation 2: Skin corrosion/irritation – Category 2
Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B Toxic to Reproduction 2: Reproductive toxicity – Category 2

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

Printing date 01/23/2024 Reviewed on 04/05/2023

Trade name: Vibra-TITE® Gasket Maker

(Contd. of page 6)